


WELL LOG BUREAU--KANSAS GEOLOGICAL SOCIETY
508 E. Murdock. Wichita, Kansas

Company - W. L. HARTMAN
Farm - Lappin No. 1

SEC. 1 T. 6 R. 21W
NW NW NW

Total Depth. 3610
Comm. 5-16-49 Comp. 8-18-49
Shot or Treated.
Contractor. H. & H. Drlg. Co.
Issued. 10-15-49

County. Graham
KANSAS



CASING:
8 5/8" 180' cem. w/140 sx.
5 1/2" 3584' cem. w/100 sx.

Elevation. _____

Production. 41 BOPD

Figures Indicate Bottom of Formations.

clay	25
shale	75
sand & shale	180
shale & shells	665
shale & sand	1200
annyd.	1230
shale	1720
anhyd.	1752
shale & shells	2180
lime & shale	2423
shale	2600
lime & shale	2953
shale	3047
lime & shale	3168
lime	3317
lime & shale	3330
lime	3590
sand	3605
granite	3605
lime	3610
Total Depth	

Tops: D. F. Corr. 2' for rotary bushing
 Topeka 3104
 Heebner 3300
 Toronto lime 3326
 Lansing, K.C. 3340
 Marmaton (B/K.C.) 3535
 Congl. 3580
 Granite wash 3582

R.T.D. 3583

Trip at 1720' Slpe Test OK SLM OK
 Slope Test @ 2427 OK SLM OK
 Slope Test @ 3000 OK SLM OK
 Trip @ 3192
 Circ. @ 3334
 Trip @ 3405
 Circ. @ 3429

Rotary Total Depth 3585' R.B. Meas.
 Circ. at 3545 & 3555 & 3573 & 3585

D.S.T. 3423-29, open 1 hr. rec. 70'
 muddy wtr. BHP 1200 $\frac{1}{2}$