


58861

SKELLY OIL CO.
John E. Mills No. 1.

SEC. 2 T. 6 R. 23 W
SW 1/4 SE
330' f SL 330' f WL SE 1/4

Total Depth. 3996'
Comm. 2-6-43 Comp. 3-1-43
Shot or Treated.
Contractor. Claude Wentworth Drlg. Co.
Issued. 3-20-43

County. Graham



CASING:
8 5/8" 305' Cem.

Elevation.

Production. Dry

Figures Indicate Bottom of Formations.

surface soil, shale, sand	0-260
shale & shells	306
shale	750
sand & shale	990
sand, shale, shells	1390
anhydrite	1450
shale & red bed	1675
sand	1750
shale	1840
shale & shells	2035
lime	2070
lime brkn	2205
lime & shale	2550
lime	2615
shale	2635
lime brkn	2690
lime	2750
lime brkn	2820
lime & shale	2910
lime brkn	2920
shale & shells	2950
lime	3005
lime brkn & shale	3055
lime	3085
lime & shale	3135
lime brkn	3330
lime	3380
lime brkn	3404
lime	3472
sand	3488
lime	3640
lime cherty	3650
lime	3695
lime & shale	3725
lime	3765
lime brkn	3794
lime & shale	3848
lime	3886
shale & lime	3936
cherty lime & shale	3963
shale red, sand, oolitic chert	3996
dolomite hd gy, finely crystalline, no poro.	3969
dolomite med sft gy, coarsely cryst.	3996
Total Depth.	

Tops: Topeka Lime 3395
Lansing Lime 3598
Arbuckle Lime 3966

probably wtr 3969-96