DAILY DRILLING REPORT

OWNERS: Abercrombie Drilling, Inc.
James M. Stewart
FARM NAME: Peel-Pratt #1
LOCATION: SE SE SW, Sec. 13-6S-23W
Graham County, Kansas
TEST: Base/K. C. - 3840 (approx.)
GEOLOGIST: Jack K. Wharton

3-17-68 Moved in and rigged up. Drilled 240' of 11" surface hole and set 7-5/8" casing @237' w/125 sx. Sunset cement. Plug was down at 9:00 p.m., 3-16-68.
Cement circulated.

3-18-68 2585 Bit #2 - Lime & Shale
T/Anh. 2031 - B/Anh. 2063

3-19-68 3160 Bit #4 - Lime & Shale

3-20-68 3620 Bit #5 - Lime

3-21-68 3680 Bit #6 - Lime

ELEVATION
2381 K. B.
2379 D. F.
2373 G. L.

SAMPLE TOPS

Heebner	3588	(-1207)			
Toronto	3611	(-1230)	B/K.C.	3821	(-1440)
Lansing	3626	(-1245)	RTD	3830	(-1449)

DST #1 (3535-3571) Open 1 hr., shut in 30 min.) Recovered 360' muddy water w/scum of oil and 1040' salt water.
IBHP - 1284, FBHP - 1211, IFP - 140, FFP - 710

3-22-68 3762 Bit #7
DST #2 (3680-3705) Open 1 hr., shut in 30 min. Strong blow. Recovered 1500' salt water. IBHP - 1285, FBHP - 1270, IFP - 148, FFP - 746.
DST #3 (3774-3782) Open 7 min. Packer seats washed out while attempting to flush tool. IBHP - 15#, No FBHP, IFP - 15#, FFP - 15#

3-23-68 3830 Rotary Total Depth
D&A. 1st plug was set @1300' w/80 sx., 2nd plug @245' w/15 sx., top plug @40' w/10 sx. Plug was down 9:00 a.m., 3-23-68.
State plugging representative - Bill Nichols.

DROPPED FROM REPORT