CFPB

TYPE

AFFIDAVIT OF COMPLETION FORM State Geological Survey

| SIDE ONE | Suite Geologicus Cu | | | Compt. |
|---|---|---|--|---|
| Two (2) copies of this mission, 200 Colorado Derby days after the completion of Attach separate letter If confidential, only file orecord and Side Two will the Applications must be mainjection and temporarily ab X Attach one copy only wineutron log, etc.). (Rules | Building, Wichita, Kans a well, regardless of of request if the informe copy. Information on be held confidential. de on dual completion, andoned wells. reline logs (i.e. elect 82-2-105 & 82-2-125) K | as 67202, wi how the well mation is to n <u>Side One</u> w commingling, rical log, s CC# (316) 26 | thin thirty was comple be held co ill be of p salt water onic log, g 3-3238. | (30) ted. nfidential. ublic disposal, amma ray No Log |
| LICENSE # 5562 | | | | |
| OPERATOR <u>Liberty Enterprise</u> | | | · | |
| ADDRESS 308 W. Mill | ADDRESS 308 W. Mill | | | |
| Plainville, Kansas | 67663 | _ FIELD | | |
| ** CONTACT PERSON Charles (PHONE 913-4 | G. Comeau 434-4686 | _ PROD. FORM | ATION Arbuch | de |
| PURCHASER Farmland Industr | ies, Inc. | _ LEASELi | ebenau | |
| ADDRESS Kansas City, Mis | WELL NO. #9 | | | |
| - | | WELL LOCAT | ION NE NE | NE |
| | Co. | <u>330</u> Ft. f | rom N | Line and |
| CONTRACTOR ADDRESS 308 W. Mill | | 330 Ft. f | rom E | Line of |
| | | the (Qt | r.)SEC 19TW | P 7s RGE 17 (|
| , | as 67663 | - WE | LL PLAT | (Office |
| PLUGGING CONTRACTOR | | | | Use Onl |
| ADDRESS | | _ | | ксс |
| | | _ | | KGS_1/ |
| TOTAL DEPTH 3304' | PBTD 3285' | _ | | SWD/REP_ PLG. |
| SPUD DATE 5-7-83 DATE | COMPLETED 5-23-83 | _ | _ 1'9 | 116 |
| ELEV: GR 1748' DF 175 | 1' KB 1753' | _ | | ' |
| DRILLED WITH (KARLE) (ROTAR | Y) XXXX TOOLS. | | | |
| DOCKET NO. OF DISPOSAL OR REUSED TO DISPOSE OF WATER FRO | M THIS LEASE | | | |
| Amount of surface pipe set a | nd cemented 8 5/8 @ 119 | DV Tool Use | d? No. | _• |
| THIS AFFIDAVIT APPLIES TO: (| Circle ONE) - Oil, Gas, | Shut-in Gas | , Dry, Disp | osal, |
| 2 7/8" 3284' | | | | |
| | FRACTURE, SHOT, CEMENT SQUEE | ZE KECORD | Donah las | erval treated |
| Amount end | d kind of material used | | Sepin into | |
| Date of first anadystics | 3 | | , | |
| Date of first production 5-23-83 | Producing method (flowing, pumping, ges Pumping | lift, etc.) | Gravity | |
| Estimated Production -I.P. | 50 bbls. Ges | Water % | Ges-oil ra | tio |

the statements and arregations contained therein

Perforations

| FILL IN WELL INFORMATION AS REC | #9 SHOW GEOLOGICAL MARKERS, LOGS RUN, OR OTHER DESCRIPTIVE INFORMATION. | | | |
|---|--|--|---|--|
| cluding depth interval tested, cushion used, time tool open, flowing and FORMATION DESCRIPTION, CONTENTS, ETC. | thut-in pressures, | s, and recoveries. BOTTOM | NAME | DEPTH |
| shale and sand shale and shales and sand shales and sand shales anhydrite anhydrite shales shales lime and shale lime and shale lime and shale lime and shale shales and lime lime and shale shale and lime arbuckle | 0' 83' 300' 1010' 1185' 1195' 1227' 1345' 1388' 1730' 2015' 2261' 2490' 2725' 2903' 3020' 3124' 3230' 3282' 3304' | 83' 300' 1010' 1185' 1195' 1227' 1345' 1388' 1730' 2015' 2261' 2490' 2725' 2903' 3020' 3124' 3230' 3282' 3304' R.T.D. | LOG TOPS Heebner Toronto Lansing Base/KC Arbuckle | 2884 (-113 2908 (-115 2928 (-117 3158 (-146 3252 (-149 |

| Report of all strings set — surface, intermediate, production, etc. CASING RECORD (New) or (New) or | | | | | | | |
|---|-------------------|------------------------------|----------------|---------------|---------------------|-------------------|----------------------------|
| Purpose of string | Size hele drilled | Size casing set (in O.D.) | Weight lbs/ft. | Setting depth | Type coment | Sacks | Type and percent additives |
| conductor string | g 17 1/2" | 13 3/8" | 48# | 82.43' | common | 100 sxs | 2%gel 3%cc |
| surface string | 12 1/4" | 8 5/8" | 24# | | 60-40 pos common | 300sxs 100 sxs | 3%cc 2%gel 3%cc 2%gel |
| production | 7 7/8" | 5 1/2" | 14# | 3303' | 60-40 pos | 150 sxs | 2%gel 8%salt 5 |
| | | | | | | | |

| LINER RECORD | | | | PERFORATION RECORD | | | |
|---------------|---------------|---------------|---------------|--------------------|----------------|--|--|
| Top, ft. | Bettem, ft. | Secks cement | Shots per ft. | Size & type | Depth interval | | |
| | | | 4 per 1/2' | | 3253-3255½ | | |
| TUBING RECORD | | | | | | | |
| Sise | Setting depth | Pecker set at | | | | | |