

SIDE ONE

13-7-18W
DOCKET NO. NR

(Rules 82-3-130 and 82-3-107)

This form shall be filed with the Kansas Corporation Commission, 200 Colorado Derby Building, Wichita, Kansas 67202, within ninety (90) days after the completion of a well, regardless of how the well was completed.

FOR INFORMATION REGARDING THE NUMBER OF COPIES TO BE FILED AND APPLICATIONS REQUIRING COPIES OF ACO-1 FORMS SEE PAGE TWO (2), SIDE TWO (2) OF THIS FORM.

F ☒ Letter requesting confidentiality attached.

C ☒ Attach ONE COPY of EACH wireline log run (i.e. electrical log, sonic log, gamma ray neutron log etc.)***Check here if NO logs were run_____.

PLEASE FILL IN ALL INFORMATION. IF NOT AVAILABLE, INDICATE. IF INFORMATION LATER BECOMES AVAILABLE, SUBMIT BY LETTER.

LICENSE # 5900 EXPIRATION DATE 6-30-84

OPERATOR Lawbanco Drilling, Inc. API NO. 15-163-22, 284

ADDRESS PO Box 289 COUNTY Rooks

Natoma, Kansas 67651 FIELD _____

** CONTACT PERSON Reva Musgrove PROD. FORMATION _____

PHONE (913) 885-4676 _____ Indicate if new pay.

PURCHASER _____ LEASE Maddy

ADDRESS _____ WELL NO. 01

DRILLING R. and C. Drilling Company, Inc. WELL LOCATION NW SE SW

CONTRACTOR 2717 Canal 990 Ft. from South Line and

ADDRESS PO Box 296 1650 Ft. from West Line of

Hays, Kansas 67601 the SW (Qtr.) SEC 13 TWP 7 RGE 18 (1)

PLUGGING R. and C. Drilling Company, Inc. WELL PLAT

CONTRACTOR 2717 Canal (Office Use Only)

ADDRESS PO Box 296 KCC _____

Hays, Kansas 67601 KGS ☒

TOTAL DEPTH 3338' PBD _____ SWD/REP _____

SPUD DATE 2-01-84 DATE COMPLETED 2-09-84 PLG. _____

ELEV: GR 1763' DF 1765' KB 1768' NGPA _____

DRILLED WITH (CABLE) (ROTARY) (AIR) TOOLS.

DOCKET NO. OF DISPOSAL OR REPRESSURING WELL BEING USED TO DISPOSE OF WATER FROM THIS LEASE _____

Amount of surface pipe set and cemented 30 its 8 5/8 DV Tool Used? _____.

TYPE OF COMPLETION THIS AFFIDAVIT APPLIES TO: (Circle ONE) - Oil, Shut-in Gas, Gas, Dry, Disposal, Injection, Temporarily Abandoned. If OWWO, indicate type of re-completion _____. Other completion _____. NGPA filing _____.

ALL REQUIREMENTS OF THE STATUTES, RULES AND REGULATIONS PROMULGATED TO REGULATE THE OIL AND GAS INDUSTRY HAVE BEEN FULLY COMPLIED WITH.

A F F I D A V I T

R. L. Finnesy, being of lawful age, hereby certifies that:

I am the Affiant, and I am familiar with the contents of the foregoing Affidavit. The statements and allegations contained therein are true and correct.

W8 10561
 OPERATOR Lawbanco Drilling, Inc. LEASE NAME Maddy SEC 13 TWP 7 RGE 18 (1)
 WELL NO 01

FILL IN WELL INFORMATION AS REQUIRED;

Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries.

Show Geological marker logs run, or other Descriptive information.

Formation description, contents, etc.	Top	Bottom	Name	Depth
---------------------------------------	-----	--------	------	-------

☐ Check if no Drill Stem Tests Run.
☐ Check if samples sent Geological Survey.

0 to 1203 Sand and Shale
 1203 to 1238 Anhydrite
 1238 to 2210 Sand and Shale
 2210 to 3229 Shale and Lime
 3229 to 3338 Shale and Lime RTD

Topeka	2715
Heebner	2924
Toronto	2948
Lansing KC	2966
Base KC	3193
Marmaton	3199
Arbuckle	3300
RTD	3338

DST # 1

Interval Tested: 3191' to 3229'. Marmaton Sand
 Times: 60-60-60-60.

Blow: Weak on both opens.

Recovery: 45' of very slightly oil-specked muddy water.

Shut-in Pressures: 1087 to 1009.

Flow Pressures: 58-68 & 68-78.

RECEIVED
 STATE CORPORATION COMMISSION

MAR 06 1984

CONSERVATION DIVISION
 Wichita, Kansas

If additional space is needed use Page 2

Report of all strings set — surface, intermediate, production, etc.

CASING RECORD (New) or (Used)

Purpose of string	Size hole drilled	Size casing set (in O.D.)	Weight lbs/ft.	Setting depth	Type cement	Sacks	Type and percent additives
Surface	12 $\frac{1}{4}$	8 5/8	24 lb	1207'	60/40 poz	500	2% gel, 3% cc

LINER RECORD

PERFORATION RECORD

Top, ft.	Bottom, ft.	Sacks cement	Shots per ft.	Size & type	Depth interval
TUBING RECORD					
Size	Setting depth	Packer set at			