15-163-00300

KANSAS WELL LOG BUREAU --- KANSAS GEOLOGICAL SOCIETY

508 EAST MURDOCK - WICHITA, KANSAS

COMPANY DEEP ROCK OIL CO.

FARM Loeffler NO. 1


SEC. 6 T. 7 R. 20W

LOC. NW NW SE

330' S. of N.L. 330' E. of W.L. of SE/4

COUNTY Rooks

KANSAS



TOTAL DEPTH 3850

COMM. 4-25-51 COMP. 5-4-51

SHOT OR TREATED

CONTRACTOR Creekmore Drlg. Co.

ISSUED 6-9-51

CASING

8 5/8" 212' cem. w/175 sx

ELEVATION 2234 DF
2236 KB

PRODUCTION Dry

FIGURES INDICATE BOTTOM OF FORMATIONS

surface clay & sand	40	cement.
sand	70	Plugging comp. 5-6-51
shale	245	
shale & shells	980	
sand & shale	1580	
shale & lime	2375	
lime	2475	
shale & lime	3409	
lime	3429	
shale & lime	3464	
lime	3655	
shale & lime	3735	
shale & sand	3784	
lime	3850	
Total Depth		

Tops:

Heebner Shale	3429
Toronto	3454
Lansing	3467
Base Kansas City	3667
Conglomerate	3710
Arbuckle	3784

DST: #1 3392-3409' Basal Section of Topeka, Tool open 1 hr. Weak steady blow. Rec. 170' salt water & rotary mud. BHP 1140#.

DST: #2 3462-3487' Top Lansing. Tool open 30 mins. Weak unsteady blow. Rec. 60' slightly gas cut mud and water. BHP 840#.

Record of Plugging
Drillers T.D. 3850
Schlumberger T.D. 3852'
Plugging Comm. 5-5-51

Filled hole with heavy mud from 3850' up to 270'. Set wood plug at 270' with ½ sack hulls on top. Put in 15' rock bridge. Cement hole to 184' with 28 sacks cement. Filled hole with mud from 184' to 60'. Put in 3' wood plug with ½ sack hulls on top. Put in 15' rock bridge on top of wood plug. Filled hole to top and into bottom of cellar with 12 sacks