


CARTER OIL CO.
Lillio List No. 1.

SEC. 10 T. 8 R. 17W
SWc SW
330' fr S & W Lines

Total Depth. 3508'
Comm. 3-29-38 Comp. 4-22-38
Shot or Treated.
Contractor. Company Tools
Issued. 5-7-38 Rotary 3508'

County. Rocks



CASING:

8 5/8" 707'

Elevation.

Production. Dry

Figures Indicate Bottom of Formations.

clay	40	lime brown	3326
sand	60	cored lime & shale	3334
shale	225	lime	3410
shale & shells	470	shale	3421
shale	510	lime	3474
sand	585	conglomerate	3489
sd shale	708	dolomite	3496
lime & sand	775	cored (odor of sul-	3506
shale & shells	795	cored lime plur)	3508
sandstone	808	Total Depth.	
lime brown	845		
sd shale & sand	875		
sand	1000	Abandoned.	
sand & red rock	1020	Arbuckle 3489-3508	
shale blue	1045		
shale red & blue	1345	Top Douglas 3135	
anhydrite	1373	Very sm sh oil 3120	
lime	1390	Sm sh gas 3324-28	
shale red & blue	1465	Cored 3328-34 full rec. No shows	
lime	1495	Very sm sh oil 3380	
shale red & blue	1620	Top Basal Penn. Cgl. 3438	
shale & shells	1650	Top Siliceous 3489	
shale blue	1670	Cored 3496-3508 Rec 5' no shows	
shale red & blue	1750		
shale & lime	1841		
shale red & blue	1850		
lime	1865		
red rock & shale	1894		
lime	1915		
shale blue & red	1950		
shale & lime	2055		
lime	2080		
shale	2090		
shale & lime shells	2145		
shale blue & red	2200		
lime	2235		
brkn lime	2293		
shale & lime	2399		
lime & shale	2492		
shale & shells	2760		
lime	2814		
brkn lime	2875		
shale & lime	2907		
brkn lime	2917		
lime	2975		
brkn lime	2994		
lime	3174		
chert	3175		
lime	3292		
lime & chert	3315		
lime	3324		