
WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
503 East Murdock, Wichita, Kansas

15-163-01390

Company- JONES, SHELBURNE & FARMER, INC. SEC. 24 T. 8 R. 18W
Farm- Pearl No. 1 NE NE SE

Total Depth. 3423
Comm. 10-18-52 Comp. 10-26-52
Shot or Treated.
Contractor.
Issued. 11-7-53

County Rooks
KANSAS



Elevation. 1994 DF

Production. IPP 85 BO & 1½% wtr.

CASING:
8 5/8" 168' cem. w/100 sx
5 1/2" 3420' cem. w/100 sx

Figures Indicate Bottom of Formations.

shale	0 -	1180
shale & red bed		1315
anhydrite		1350
shale & shells		1800
shale & lime		2880
lime & shale		3165
lime		3415
arbuckle		3420
arbuckle		3423
Total Depth		

Tops:


Heebner	3117
Toronto	3137
Lansing	3157
Arbuckle	3415

Form 1002A

OPERATOR Jones, Shelburne & Farmer, Inc.

ADDRESS Russell, Kansas

640 Acres
N



Locate well correctly

COUNTY Rooks, SEC 24 TWP 8S RGE 18W

COMPANY OPERATING Jones, Shelburne & Farmer, Inc.

OFFICE ADDRESS Russell, Kansas

FARM NAME Pearl WELL NO. 1

DRILLING STARTED 10-18 19 52 DRILLING FINISHED 10-24 19 52

DATE OF FIRST PRODUCTION COMPLETED

WELL LOCATED NE ¼ NE ¼ SE ¼, North of South Line and ft. East of West Line of Quarter Section

Elevation (Relative to sea level) DERRICK FLOOR 1994 GROUND

CHARACTER OF WELL (Oil, gas or dryhole) Oil

FARM NAME Pearl WELL NO. 1 COUNTY Rooks SEC 24 TWP 8S RGE 18W

OIL OR GAS SANDS OR ZONES

Name	From	To	Name	From	To
1			4		
2			5		
3			6		

Perforating Record If Any

Formation	From	To	No. of Shots

Shot Record

Formation	From	To	Size of Shot

CASING RECORD

Amount Set								Amount Pulled		Packer Record	
Size	Wt.	Thds.	Make	Ft.	In.	Ft.	In.	Size	Length	Depth Set	Make
8 5/8	24	8	LL	1	8			None			

Liner Record: Amount Kind Top Bottom

CEMENTING AND MUDDING

Size	Amount Set Ft.	Amount Set In.	Sacks Cement	Chemical Gal.	Chemical Make	Method of Cementing	Amount	Mudding Method	Results (See Note)
8 5/8	1	8	100						
5 1/2	3420		100						

Note: What method was used to protect sands if outer strings were pulled?

NOTE: Were bottom hole plugs used? If so, state kind, depth set and results obtained

TOOLS USED

Rotary Tools were used from feet to Cable tools were used from feet to feet, and from feet to feet, and from feet to

Type Rig

INITIAL PRODUCTION TEST

Describe initial test: whether by flow through tubing or casing or by pumping

Amount of Oil Production bbls. Size of choke, if any Length of test Water Production bbls. Gravity of oil Type of Pump if pump is used, describe

FORMATION RECORD

Give detailed description and thickness of all formations drilled through, contents of sand, whether dry, water, oil or gas.

Formation	Top	Bottom
Shale	0	1180
Shale & Red Bed	1180	1315
Anhydrite	1315	1350
Shale & Shells	1350	1800
Shale & Lime	1800	2880
Lime & Shale	2880	3165
Lime	3165	3415
Arbuckle	3415	3420

TOPS:

Elevation 1994 R. B.
Heebner 3117
Toronto 3137
Lansing 3157
Arbuckle 1415
Total Depth 3420

MAY 16 1985

State Geological Survey
WICHITA BRANCH

RECEIVED
STATE CORPORATION COMMISSION
MAY 15 1985
CONSERVATION DIVISION
Wichita, Kansas

I, the undersigned, being first duly sworn upon oath, state that this well record is true, correct and complete according to the records of this office and to the best of my knowledge and belief.

John C. Farmer
Vice-President
Name and title of representative of company

Subscribed and sworn to before me this 30th day of October 1952, 19

My Commission expires April 23, 1956 Bonnie Berryhill
Notary Public

27-8-18W