

KANSAS WELL LOG BUREAU --- KANSAS GEOLOGICAL SOCIETY

508 EAST MURDOCK - WICHITA, KANSAS

15-163-02460

COMPANY HARRY GORE

SEC. 35 T. 8 R. 19W

FARM F. Slansky

NO. 2

LOC. SW NW SE

TOTAL DEPTH 3490' R. B.

COMM. 4-2-51


COMP. 4-11-51

SHOT OR TREATED

CONTRACTOR Strain Drilling Co.

ISSUED 5-12-51

COUNTY Rooks KANSAS



CASING

8-5/8" 153' w/100 sx5 cem.

ELEVATION 1973 DF

PRODUCTION dry

FIGURES INDICATE BOTTOM OF FORMATIONS

post rock & shale	70
blue shale & shells	153
shale & shells	650
shale & sand	780
Pyrite, shale	890 ✓
sand	1135
red bed	1335
red bed & shale	1410
anhydrite	1450
shale & shells	1570
shale & shells	1865
shale & lime	1960
lime & shale	2140
lime & shale	2395
lime	2500
lime & shale	3065
lime	3418
shale	3430
shale & lime	3464
lime	3490
Total depth (R. B.)	

Tops: Rotary bushing measurements

Anhydrite	1410
Topeka	2946
Heebner	3175?
Dodge	3175?
Lansing (K. C.)	3192
Base K. C.	3418
Conglomerate	3455
Arbuckle	3484

All meas. rotary bushing