

KANSAS GEOLOGICAL SOCIETY
KANSAS WELL LOG BUREAU - KANSAS WELL SAMPLE BUREAU
KANSAS GEOLOGICAL SOCIETY BUILDING
508 EAST MURDOCK - WICHITA, KANSAS

COMPANY **NADEL & GUSSMAN**

FARM **Jamison**

NO. **1**


SEC. **20 T. 8 R. 27W**

LOC. **C NE SW**

15-179-20140

COUNTY **Sheridan**

KANSAS



TOTAL DEPTH **4125'**

COMM. **10-12-67**

COMP. **10-20-67**

SHOT OR TREATED

CONTRACTOR **Murfin Drlg.**

ISSUED **12-9-67**

CASING

20	10	
15	8 5/8"	231' cem w/ 160 sx
12	6	
13	5	

ELEVATION **2671' KB**

PRODUCTION **DRY/BKC**

FIGURES INDICATE BOTTOM OF FORMATIONS

		Sample Tops:	
80	Surface Clay & Sand	Anhydrite	2340' (+ 331)
220	Sand	Base/Anhydrite	2375' (+ 296)
235	Shale	Topeka	3610' (- 939)
1120	Sand & Shale	Hoebner	3824' (-1153)
1845	Shale	Toronto	3852' (-1181)
2340	Shale & Sand	Lansing	3866' (-1195)
2375	Anhydrite	Base/Kansas City	4092' (-1421)
2613	Shale	Total Depth	4125' (-1454)
2820	Shale-Shells		
2985	Shale & Lime		
3115	Lime & Shale		
3225	Shale Lime		
3858	Lime & Shale		
3900	Lime		
4125	Lime & Shale		

DST #1 3893-3900' Op. 2 hrs., rec. 45' heavy oil-cut mud, 90' moderate oil-cut mud, 150' muddy SW. IBHP 1256/30", FBHP 1071/30", IFP 27, FFP 144.

DST #2 3478-3523', hook-wall pecker, Op. 90", rec. 180' SW, 800' drilling mud, IBHP 1157/30", FBHP 1116/30", IFP 270, FFP 496.