

PHILLIPS PETRO.CO.
Anderson No. 1.

15-163-00032
SEC.28 T.9 R.16W
CWL SW SW

Total Depth. 3590' PB 3365'
Comm. 5-15-41 Comp. 6-2-41
Shot or Treated.
Contractor. Clay Bros.Drlg.Co.
Issued. 7-19-41

County. Rocks



CASING:
10 3/4" 102'3" Cem.
5 1/2" 3367' Cem.

Elevation.

Production. Dry

Figures Indicate Bottom of Formations.

no log	25
sand-rock & clay	58
sand rock	88
surface rock	110
shale & shells	342
shale,shell,sand	780
shale	870
shale & pyrite	900
shale & shells	944
sand & shells	977
red bed & shells	1275
anhydrite gyp	1310
shale & shells	1323
shale,shells,red bed, & anhydrite	1462
variegated shale & shells, strks of anhydrite & gyp	1665
shale & shell	1795
shale & anhydrite	1853
anhydrite,shale,lime	2037
shale brkn anhydrite	2080
lime & shale	2140
shale & lime shells	2233
variegated shale, anhydrite & gyp	2277
shale brkn lime	2372
shale & lime	2460
variegated shale, anhydrite & lime shells	2544
shale & lime	2608
shale & shells	2834
shale,shells,lime	2937
shale & lime	3253
lime,chat,shale	3290
lime & shale	3338
core (lime)	3348
lime	3356
lime & chert	3386
lime & shale	3507
shale & chert	3550
shale & lime	3593
Corr. 3593=3576	
shale & lime	3576-3590
Total Depth.	

Plugged back to 3365