TYPE

SIDE ONE

•	_	•	~	••	-					
		C	o	m	p	t	۰			

F C	Two (2) copies of this form shall be filed with mission, 200 Colorado Derby Building, Wichita, Kansa days after the completion of a well, regardless of heattach separate letter of request if the inform If confidential, only file one copy. Information on record and Side Two will then be held confidential. Applications must be made on dual completion, conjection and temporarily abandoned wells. **Attach one copy only wireline logs (i.e. electroneutron log, etc.). (Rules 82-2-105 & 82-2-125) KC	s 67202, within thirty (30) ow the well was completed. ation is to be held confidential. Side One will be of public ommingling, salt water disposal, ical log, sonic log, gamma ray
	LICENSE # 5562 EXPIRATION DATE	6-30-83
	OPERATOR Liberty Enterprises Inc.	API NO. 15-163-21,905
	ADDRESS 308 W. Mill	COUNTY Rooks
_	Plainville, Kansas 67663	FIELD Cameau
	** CONTACT PERSON Charles G. Comeau PHONE 913-434-4686	PROD. FORMATION Cedar Hill
_	PURCHASER ADDRESS State Geological Survey WICHITA BRANCH	LEASE Comeau
	ADDRESS State Geologica BRANCH WICHITA BRANCH	WELL NO. #3 SWD
	Wichin	WELL LOCATION SE NW SW
	DRILLING Pioneer Drilling Co.	1650 Ft. from S Line and
	CONTRACTOR ADDRESS 308 W. Mill	990 Ft. from W Line of
	Plainville, Kansas 67663	the SW (Qtr.) SEC 25 TWP 9s RGE 18 (W).
	PLUGGING	WELL PLAT (Office
	CONTRACTOR	Use Only)
	ADDRESS	KCCKGS
	TOTAL DEPTH 20551 PRTD 1302'	SWD/REP
	101111 201111 3033	25PLG
	SPUD DATE 12-6-82 DATE COMPLETED 1-10-83	
	ELEV: GR 2139' DF 2142' KB 2144'	x
	DRILLED WITH (CABLE) (ROTARY) (AKRX TOOLS. DOCKET NO. OF DISPOSAL OR REPRESSURING WELL BEING USED TO DISPOSE OF WATER FROM THIS LEASE	
	Amount of surface pipe set and cemented 248'	DV Tool Used? No .
	THIS AFFIDAVIT APPLIES TO: (Circle ONE) - Oil, Gas, Injection, Temporarily Abandoned, OWWO. Other	Shut-in Gas, Dry, Disposal,
	ALL REQUIREMENTS OF THE STATUTES, RULES AND REGULATION AND GAS INDUSTRY HAVE BEEN FULLY COMPLIED WITH.	ONS PROMULGATED TO REGULATE THE OIL

A F F I D A V I T

FEB 4 533

Charles G. Comeau , being of lawful age, hereby certifies that:

I am the Affiant, and I am familiar with the contents of the fregoing Affidavit. The statements and allegations contained therein are true

ACO-1 WELL HISTORY (PA)

OPERATOR Liberty Enterprises Inc. LFASE Comeau

SEC.25 TWP.9s RGE.18

FILL IN WELL INFORMATION AS REQUIRED:

WELL NO. #3

SHOW GEOLOGICAL MARKERS, LOGS RUN, OR OTHER DESCRIPTIVE INFORMATION. Show all important zones of porcelty and contents thereof; cored intervals, and all drill-stem tests, including depth interval testoc, cushion used, time tool open, flowing and shut-in pressures, and recoveries. FORMATION DESCRIPTION, CONTENTS, ETC. NAME DEPTH TOP BOTTOM Y Check if no Drill Stem Tests Run. Anhydrite 1477 (+667) Topeka 3078 (-934) 3291 (-1147) Heebner Toronto 3310 (-1166) 0 ' 250 **'** sand and shale Lansing 3333 (-1189) shales and sand 250 ¹ 3559 (-1415) 572**'** Base KC shale and sand 572**'** 1475' Arbuckle 3619 (-1475) anhydrite 1475' 1503' anhydrite 1509' 1503' 1825' shale 1509' shales and lime 2273' 1825' shale and lime 2273' 2315' shale and lime 2315' 2365' lime and shale 2365' 2707' lime and shale 2707' 2880' lime and shale 3030' 2880 ' lime and shale 30301 3141' lime and shale 3141' 3186' lime and shale 3186' 3286' lime and shale 3370' 3286' lime and shale 3370' 34321 lime and shale 3432' 3499' lime and shale 3499' 3548 lime and shale 3548 3635' lime and shale 3635' 3655' 3655' R.T.D

Report of all strings	set — surface,	intermediate,	production, et	c. CASING	RECORD (New)	or (tigge	i ¿)
Purpose of string	Size hole drilled	Size casing set	Weight lbs/ft.	Setting depth	Type coment	Sacks	Type and percent additives
surface casing	12 1/4"	8 5/8"	20#	248'	60-40 pos	140	2%gel 3%cc
production	7 7/8"	4 1/2"	9.5	1302'	A.S.C.	300	lightweight
				'			
			,				

If additional space is needed use Page 2, Side 2

	LINER RECOR	D	PERFORATION RECORD					
Top, ft.	Bottom, ft.	Secks cement	Shots per ft.	Size & type	Depth Interval			
			1 per 1'		1170-1190			
•	TUBING RECO	RD						
Size	Setting depth	Packer set at						
2 3/8"	1050'	1050'			1			