


G.C.F.

DUWE & FARRIS
Sutor No. 1.SEC. 28 T. 9 R. 19W
SWc NE

15-103-03705

County. Rocks

Total Depth. 3735'
Comm. 5-22-38 Comp. 6-6-38
Shot or Treated.
Contractor.
Issued. 8-6-38

AUG 6. 1938

CASING:

114' surface pipe

Elevation.

Production. Dry

Figures Indicate Bottom of Formations.

shale	10	lime shells & shale	3075
sand	38	lime	3095
sand & shale	65	shale drk sticky	3102
shale	135	shale	3118
shale & shells	300	lime	3139
shale sticky	420	shale	3146
shale & shells	590	lime	3406
sdv shale	760	lime hrd	3427
sand	935	lime	3548
lime brkn	955	lime brkn	3566
shale & lime	1055	lime	3590
sand shale	1300	brkn lime & shale	3601
shale red	1500	lime	3655
shale	1580	conglomerate	3675
anhydrite	1621	lime shale	3706
shale & lime	1684	lime	3723
shale & shells	1940	lime Siliceous	3735
salt	1958	Total Depth.	
shale & lime	2105		
shale lime & shells	2199		
shale & shells	2210		
lime	2248		
shale	2263		
lime	2274		
shale & lime	2295		
lime	2360		
lime hrd	2399		
lime	2416		
lime & shale brks	2462		
shale & lime	2500		
lime	2589		
shale	2619		
lime sdv red	2635		
lime	2788		
lime hrd	2811		
lime	2864		
shale sticky	2897		
shale & lime	2960		
lime	2990		