


WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY
412 Union National Bk. Bldg., Wichita, Kansas

Company - CONTINENTAL OIL CO.
Farm - O.E. Trexler No. 5.

SEC. 15 T. 9 R. 21 W
NWc NE
3 30'E 330'S N $\frac{1}{4}$ Cor.

Total Depth. 3702' (CF 3700')
Comm. 4-7-44 Comp. 5-1-44
Shot or Treated.
Contractor. Parker Drlg. Co.
Issued. 8-5-44

County. Graham
KANSAS



CASING:
10 $\frac{3}{4}$ " 239' Cem.
6" 3670' Cem.

Elevation. _____

Production. Phy. Pot. 425 B.

Figures Indicate Bottom of Formations.

| | |
|--------------------|------|
| shale & sand | 40 |
| shale & shells | 1020 |
| sand & shells | 1036 |
| sand & shale | 1450 |
| shale & shells | 1605 |
| lime | 1625 |
| anhydrite | 1640 |
| shale & shells | 2196 |
| lime & shale bro | 2342 |
| shale & shells | 2530 |
| lime | 2544 |
| lime bro & shale | 2610 |
| shale & shells | 2725 |
| lime | 2777 |
| lime bro & shale | 2830 |
| lime bro | 2998 |
| lime bro & shale | 3079 |
| lime bro | 3231 |
| lime bro & shale | 3284 |
| lime | 3416 |
| lime bro | 3485 |
| lime w/shale strks | 3530 |
| lime | 3678 |
| lime & shale | 3664 |
| lime | 3702 |
| Total Depth. | |

Tops:
Dolomite 3668
Pennsylvania Sand 3680

3692
2218

5-12-44 Drilled out cement
plug & hole filled 1000' w/oil
in 24 hrs. Hole caving.
Deepened to 3696 & cleaned out cavings
5-23-44 ran & gravel packed 60' 4" of
4 $\frac{1}{2}$ " liner; set at 3690
5-29-44 Deepened to 3700' in
Pennsylvania Sand.
5-30-44 Acidized w/500 gals.
through 4 $\frac{1}{2}$ " liner frm 3670'-
3700

6-4-44 Established 24 hr. phy
pot. of 425 Bbls oil.
Total Depth 3700 in Penn. Sand

Note: Footages from cement floor
except formations