


WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY 15-065-01427
508 E. Murdock Wichita, Kansas

Company - CITIES SERVICE OIL -
Farm - Seefeld No. 1

SEC. 18 T. 9 R. 21W
SE SE NE
330' N & 330' W of E/4 Cor.

Total Depth. 3800
Comm. 4-22-50 Comp. 5-8-50
Shot or Treated. None
Contractor. R. W. Rine Drlg. Co.
Issued. 6-24-50

County. Graham
KANSAS



CASING:
8 5/8" 201' cem. w/150 sx
5 1/2" 3793' cem. w/175 sx

Elevation. 2296' Ind.

Production. Drawdown Pot. 3000
Oil & NW

Figures Indicate Bottom of Formations.

surface clay & sand	100
shale	201
shale & shells	1015
shale, sand & shells	1290
sand	1510
shale & shells	1790
anhydrite	1830
shale & shells	2090
lime & shale	2320
shale & shells	2460
lime & shale	3095
lime	3310
lime & shale	3420
lime	3793
3793 RTD= 3796 SIM	
lime	3800
Total depth	

Corr. Tops:	
Hoebner	3458
Dodge	3479
Lansing	3494
Arbuckle	3791
Penetration	9'
Total depth	3800

Fillup:
65' oil in 1 hr. 20 mins. at
3796
1640' oil in 3 hrs. 5 mins. at
3800
2400' oil in 3 hrs. 35 mins.
2820' oil in 4 hrs. 5 mins.

Remarks:
Draw-down Potential: 3000
Oil & no water/24 hrs
Ind. Capacity 4245 bbls.
7 7/8" rotary hole.