

WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas


15-003-03413

Company- CITIES SERVICE OIL CO.
Farm- Holzhauser "B" No. 4

SEC. 26 T. 9 R. 22W
NW SW NE
990' N & 330' E of Cent.

Total Depth. RTD 3807 SLM 3806
Comm. 4-1-53 Comp. 4-10-53
Shot or Treated.
Contractor. R. W. Rine Drilling Co.
Issued. 6-6-53

County Graham
KANSAS



CASING:

8 5/8 set at 255' w/ 200 sx cement
5 1/2 set at 3806' w/ 175 sx cement

Elevation. 2375

Phys.
Production Pot. 259 BO, 29 BW

Figures Indicate Bottom of Formations.

sand & shale	255
shale, shells & sand	1853
anhydrite	1890
shale & shells	2445
lime & shale	3085
lime	3155
lime & shale	3465
sandy lime & shale	3555
lime	3595
lime & shale	3645
lime (RTD)	
3807 RTD = 3806 SLM	3806

Total Depth

TOPS: (corrected)

Topeka	3371
Heebner	3543
Dodge	3565
Lansing	3580
Base KC	3803

Perf. 48 sh. 3753-65; 97' fld. in 2 hrs.
41 sh. 3620-30
36 sh. 3582-91

277' fluid in 4 hrs. 10 min.
962' oil, 69' water in 16 hrs.

Acid: 1500 gals. 3753-65
1000 gals. 3620-30
1000 gals. 3582-91

PUMPED: 229 oil, 45 water, 24 hrs.