

State Geological Survey
WICHITA BRANCH

AFFIDAVIT AND COMPLETION FORM

29-9-22W

ACO-1

This form must be filed in triplicate with the Kansas Corporation Commission, 200 Colorado Derby Building, Wichita, Kansas 67202, within five days after the completion of the well, regardless of how the well was completed. Circle one: Oil, gas, dry, SWD, OWWO, injection. Please type. Complete ALL sections. Applications must be filed for dual completion, commingling, salt water disposal and injection. Attach wireline logs (i.e. electrical log, sonic log, gamma ray neutron log, etc.) KCC#-(316) 263-3238.

OPERATOR Arrowhead Petroleum, Inc. API NO. OWWO 15-065-00570-0001
 ADDRESS P. O. Box 8287 - Munger Station COUNTY Graham
Wichita, Kansas 67208 FIELD unknown
 **CONTACT PERSON Paul A. Seymour, III LEASE Jeffers


PHONE 681-3921
 PURCHASER Mobil Oil Company WELL NO. #3
 ADDRESS P. O. Box 900 WELL LOCATION SE SE SE
Dallas, Texas Ft. from _____ Line and
Ft. from _____ Line of

DRILLING CONTRACTOR Big Springs Drilling, Inc. the SEC. 29 TWP. 9S RGE. 22W

ADDRESS P. O. Box 8287 - Munger Station
Wichita, Kansas 67208

PLUGGING CONTRACTOR _____
 ADDRESS _____

TOTAL DEPTH 3870' PBTD _____
 SPUD DATE 4-11-81 DATE COMPLETED 4-13-81
 ELEV: GR 2384 DF KB



WELL PLAT
 (Quarter) or (Full) Section - Please indicate.

KCC _____
 KGS _____

DRILLED WITH (CABLE) (ROTARY) (AIR) TOOLS
 Report of all strings set — surface, intermediate, production, etc. (New) / (Used) casing.

Purpose of string	Size hole drilled	Size casing set (in O.D.)	Weight lbs/ft.	Setting depth	Type cement	Sacks	Type and percent additives
*Washdown	12 1/4"	8 5/8"	20#	163'	unknown	unknown	unknown
Production	7 7/8	4 1/2"	9.5#	3869'	60-40 POZ	125 SX	

LINER RECORD			PERFORATION RECORD		
Top, ft.	Bottom, ft.	Sacks cement	Shots per ft.	Size & type	Depth interval
TUBING RECORD			4 shots	DP Jets	3820-3824
Size	Setting depth	Packer set at			
2"	3829				

ACID, FRACTURE, SHOT, CEMENT SQUEEZE RECORD	
Amount and kind of material used	Depth interval treated
250 gals mud acid	3820-3824
2,000 gals 28% w/14 perf balls	3820-3824

