

TO: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
130 SOUTH MARKET, SUITE 2078  
WICHITA, KANSAS 67202

API Well Number: 15-017-19004-00-00  
Spot: NE Sec/Twnshp/Rge: 34-19S-7E  
5173 feet from S Section Line, 1339 feet from E Section Line  
Lease/Unit Name: STARKEY Well Number: 1-X  
County: CHASE Total Vertical Depth: 218 feet

Operator License No.: 5399  
Op Name: AMERICAN ENERGIES CORPORATION  
Address: 155 N. MARKET, STE 710  
WICHITA, KS 67202

Surface Casing Size: 5.1875 feet: 218 38.5 sx outside, 38.5 sx inside  
*#35<sup>00</sup>*

Well Type: GAS UIC Docket No: \_\_\_\_\_ Date/Time to Plug: \_\_\_\_\_  
Plug Co. License No.: 30437 Plug Co. Name: UNITED CEMENTING AND ACID CO., INC.  
Proposal Rcvd. from: LAWRENCE W. JACKSON Company: AMERICAN ENERGIES CORP. Phone: (620) 793-2146

Proposed  
Plugging  
Method:

IN ACCORDANCE WITH THE KANSAS CORPORATION'S RULES AND REGULATIONS.

RECEIVED  
KCC DISTRICT #2

NOV 20 2003

WICHITA, KS

Plugging Proposal Received By: MICHAEL WILSON  
Date/Time Plugging Completed: 11/18/2003 1:10 PM

WitnessType: Plugging Operations 100% Witnessed (Complete)  
KCC Agent: BILL JOHNSON

**Actual Plugging Report:**

Ran 1" tubing to a reported depth of 204' by driller, (when tubing was pulled, joints equal 225' - 7' = 218' TD). Spotted 38-1/2 sx of 60/40 posmix 4% gel inside. Washed down outside of 5-3/16" casing to a depth of 53', gravel at 40', shale at 43', and limestone 53'. Spot tubing @ 45', cement with 38-1/2 sx.

Actual total depth vertical depth, surface casing, and type of rock units encountered could not be verified. An estimate of 218' was used as TVD for plugging documentation.

RECEIVED  
KANSAS CORPORATION COMMISSION

NOV 25 2003


CONSERVATION DIVISION  
WICHITA, KS

Remarks: USED 60/40 POSMIX WITH 4% GEL BY UNITED CEMENTING CO. INC. TICKET #5038

Plugged through: TBG

District: 02

Signed

  
(TECHNICIAN)

INVOICED

DATE 11-25-03

INV. NO. 2004060823