

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-051-20697-00-01
Spot: NESWSE Sec/Twnshp/Rge: 26-14S-19W
990 feet from S Section Line, 1650 feet from E Section Line
Lease/Unit Name: COPELAND Well Number: 1
County: ELLIS Total Vertical Depth: 3707 feet

Operator License No.: 31933
Op Name: M E KLEIN & ASSOCIATES, INC
Address: PO BOX 721436
NORMAN, OK 73070

Production Casing Size: 5.5 feet: 3704 w/100 sxs cmt
Surface Casing Size: 8.625 feet: 1334 w/600 sxs cmt

120 48

Well Type: EOR UIC Docket No: E23540.5 Date/Time to Plug: 12/11/2003 11:00 AM
Plug Co. License No.: 99998 Plug Co. Name: COMPANY TOOLS
Proposal Rcvd. from: CARL ZIMMERMAN Company: M.E. KLEIN & ASSOCIATES, INC. Phone: (405) 321-7171

Proposed Plugging Method: Ordered out 245 sxs 60/40 pozmix - 10% gel - 29 sxs gel - 500# hulls.

Plugging Proposal Received By: HERB DEINES WitnessType: Plugging Operations 100% Witnessed (Complete)
Date/Time Plugging Completed: 12/11/2003 6:30 PM KCC Agent: JAY PFEIFER

Actual Plugging Report:

TIH with tubing to 2800' - mixed and pumped 20 sxs cement with 500# hulls.
Pulled up out of cement - spotted 15 sxs gel.
Pulled up to 1325' - circulated cement with 100 sxs cement.
POOH. Topped with 15 sxs cement.
Max. P.S.I. 800#. S.I.P. 800#.
Hooked up to the annulus and pumped 9 sxs gel.
S.I.P. 900#.

RECEIVED
DEC 19 2003
KCC WICHITA


Remarks: ALLIED CEMENTING COMPANY.

Plugged through: TBG

District: 04

1002

Signed



(TECHNICIAN)

INVOICED

Form CP-2/3

DATE 12-22-03

INV. NO. 2004060972

DEC 17 2003

BEACON RESOURCES CORP. #1 COPELAND 26-14-19W
 WICHITA, KANSAS NE SW SE
 CONTR B & B DRILLING, INC. CTY ELLIS
 GEOL JAY DIRKS FIELD ANTONINO SQ. EXT.
 E 2069 KB CM 11/23/70^{CARD} ISSUED 7/15/71 IP P 15 BOPD + WTR
 LKC 3508-12

| | | | |
|--|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |

API 15-051-20,697

| LOG | TOPS | DEPTH | DATUM | |
|--|------|-------|-------|--|
| ANHY | | 1319 | + 750 | 8 5/8" 1334/600sx; 5 1/2" 3704/100sx |
| HEEB | | 3330 | -1261 | DST(1) 3390-3410(LANS)/30-30-30-30, 270' SW, BHP 824-824#, FP 40-144# |
| LKC | | 3376 | -1307 | DST(2) 3414-3434(LANS)/30-30-30-30, 400' SW(NS), BHP 848-824#, FP 40-144# |
| CONG | | 3670 | -1601 | DST(3) 3498-3526(LANS)/30-30-30-30, 1200' GIP, 90' OCM, 50' MO, 10' GO, BHP 424-352#, FP 48-96# |
| *CONG SD | | 3703 | -1634 | DST(4) 3524-42(LANS)/30-30-60-30, 120' GIP, 65' HO & GCM, BHP 304-336#, FP 32-40# |
| LTD | | 3703 | -1634 | DST(5) 3542-3568(LANS)/30-30-30-30, 20' M W/SP OIL, BHP 135-104#, FP 48-64# |
| RID | | 3707 | -1638 | DST(6) 3668-3707(ARB)/30-30-30-30, 240' HO & GCM, 60' HO & GCM W/TR WTR, 120' O & GCW, 60' WTR, BHP 1126-1126#, FP 80-256# |
| *SAMPLE TOP | | | | |
| MGT, CO 3707 TD FU 500' OIL & 1500' WTR/14 HRS SWB 7 1/2 BFPH 70% W, PB 3680, PF(LANS) 12/3602-05 250 MCA SWB DWN SWB 2 BPH W/SC DEAD OIL, PB 3575, PF(LANS) 16/3552-56 250 MCA SWB DWN SWB 3/4 BOPH/3 HRS 1500 28% AC SWB DWN SWB 7 1/2 BFP/1ST HR 12% AC WTR, SWB 4 1/2 BO N/W | | | | |

INDEPENDENT OIL & GAS SERVICE
 WICHITA, KANSAS (OVER)