DISTRICT CONSERVATI	ION AGENT'S REPORT
TO:	
State Corporation Commission Conservation Division 800 Bitting Building	20-00-00
Wichita, Kansas	15-147-00078-00-00
	FILE NO. 68-22
	LOCATION SW SE SW
	SEC. 7 TWP. 1 RGE. 18
Dry Hole x Abandoned Oil Well	Abandoned Gas Well
I have today completed supervision of	plugging of:
Well No. 1 Lease Hec	tor
Operator Honaker Drg Co, INC. A	
Fieldc	ounty Phillips
Total Depth 3490 Feet.	
(Describe briefly the manner in	which the well was plugged)
8 5/8" at 140' circulated with 1	.25 sax cement - 51 at 3490
with 175' sax cement behind. Lan	
perforations at 3362.	
Filled with sand to 3350', set 4	sax cement with dump bailer.
pulled 2511' 5분", filled hole wi	The state of the s
and 15 sax cement, filled with m	
cement to bottom cellar.	and provided the secondary was the contemporary of the second of the secondary of the secon
the state of the s	in the second se
The state of the s	Silver COMMISSION
	APR 2 4 1951
FPLUGGING .	Wickite, Kanese
PHE SEC 7-11-18W	District Conservation Agent
NOOK PAGE -	Date 4-19-51