

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-163-20257-00-00
Spot: NENESW Sec/Twnshp/Rge: 3-10S-20W
2310 feet from S Section Line, 2970 feet from E Section Line
Lease Name: NUTSCH Well #: 6
County: ROOKS Total Vertical Depth: 3802 feet

Operator License No.: 5363
Op Name: BEREXCO, INC.
Address: PO BOX 20380
WICHITA, KS 67208

PROD Size: 5.5 feet: 3798 150 SX CMT
SURF Size: 8.625 feet: 219 140 SX CMT

123⁵⁷

Well Type: OIL UIC Docket No: _____ Date/Time to Plug: 02/12/2004 9:00 AM

Plug Co. License No.: 99998 Plug Co. Name: COMPANY TOOLS

Proposal Rcvd. from: BOB GRANT Company: BEREXCO, INC. Phone: (785) 628-6101

Proposed Plugging Method: Ordered out 400 sxs 60/40 pozmix - 10% gel - 600# hulls.
Fluid level 285'. DV Tool at 1720' w/325 sxs.
Squeeze at 1471' w/25 sxs.
Top of fish (tubing) at 3211'.
Casing leak at 2314' - 2619'.

Plugging Proposal Received By: CASE MORRIS
Date/Time Plugging Completed: 02/12/2004 4:00 PM

Witness Type: COMPLETE (100%)
KCC Agent: RICHARD WILLIAMS

Actual Plugging Report:

M.I.R.U. Karst Well Service ran tubing to 3185'.
Allied pumped 70 sxs 60/40 pozmix-10% gel with 200# hulls, followed with 50 sxs neat cement.
Pulled tubing to 1585'. Allied pumped 130 sxs cement with 400# hulls.
Cement circulated. PTOH.
Squeezed with 20 sxs cement.
Max. P.S.I. 500#. S.I.P. 500#.
Hooked up to backside - instant 500#.

Perfs:

Top	Bot	Thru	Comments
3756	3802		
3657	3677		
3627	3653		
3577	3597		
3533	3557		
3500	3522		

RECEIVED

FEB 19 2004

KCC WICHITA

Remarks: ALLIED CEMENTING COMPANY.

Plugged through: TBG

District: 04

Signed Richard Williams
(TECHNICIAN)

INVOICED
DATE 2-19-04
TEL. NO. 2004061198

Form CP-2/3

FEB 18 2004

OKMAR OIL COMPANY #6 NUTSCH 3-10-20W
 WICHITA, KS. NE NE SW
 Contr. B & B DRLG. CO., INC. Cty. ROOKS
 Geol. FROSTY COX Pool MARCOTTE
 E. 2253 KB Cm. 10/4/69 Cp. 12/11/69 IPPMP 50 BOPD + W
 NAT/ARB 3798-3802

API 15-163-20,257

SMP Tops	Depth	Datum	Csg.
			8" 219/140 sx; 5 1/2" 3798
ANH	1718	+ 535	DST 3502-22/1', 90' M/S60, BHP 1086-1068#, FP 18-54#
B ANH	1761	+ 492	DST 3533-57/2', 860' GIP, 10' HOCM
TOP	3265	-1012	60' VSO CM, 120' THIN MD,
HEEB	3469	-1216	BHP 187-177#, FP 36-109#
TOR	3487	-1234	DST 3577-91/2', 250' OCM (25%
LANS	3507	-1254	OIL) 60' THIN M, BHP 338-
ARB	3797	-1544	267#, FP 18-54#
RTD	3802	-1549	DST 3627-53/2', 180' OIL, 60' HO&
			GCM, 70' GCM, BHP 819-748#
			FP 27-142#
			DST 3657-77/90", 60' M, BHP 116-
			116#, FP 18-53#
			DST 3756-3802/1', 2780' OIL, BHP
			1067-1067#, FP 552-1066#
			CO 3802 TD, PMP 50 BO + W NAT

INDEPENDENT OIL & GAS SERVICE
 WICHITA, KANSAS

4310 W