

4-032075

7-19-95

E-17,599-0005
API Number: 15-147-20,092 -00-01

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

C W2 SW /4 SEC. 10 , 01 S , 18 W
1320 feet from S section line
4620 feet from E section line

Operator license# 5352

Lease: Wittfoth Well # 1

Operator: Baird Oil Company, Inc.

County: Phillips 116.19

Address: P.O. Box 428
Logan, Kansas 67646

Well total depth 3575 feet
Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8 5/8 Inch @ 201 feet

Aband. oil well , Gas well , Input well X, SWD , D & A

Plugging contractor: Allied Cement Company License# -

Address: Russell, Kansas 67665

Company to plug at: Hour: A.M. Day: 19 Month: July Year: 1995

Plugging proposal received from: Jim Baird

Company: Baird Oil Company, Inc. Phone:

Were: Order 300 sxs 60/40 pozmix - 10% gel - 500# hulls.

RECEIVED
STATE CORPORATION COMMISSION

SEP 01 1995

Plugging Proposal Received by: Carl Goodrow

CONSERVATION DIVISION
WICHITA, KANSAS

Plugging operations attended by agent? All [X], Part [], None []

Completed: Hour: 12:00 P.M., Day: 19, Month: July, Year: 1995

Actual plugging report: 8 5/8" set at 201' with 175 sxs. 5 1/2" set at 3574' with 200 sxs. PBTD 3542'. Prod perms 3369' - 3489'. Critical area control shots at 1125' and 1680' Squeezed 5 1/2" with 250 sxs cement blend with 450# hulls mixed in to Max. P.S.I. 100#. Close in P.S.I. 0#. Squeezed 8 5/8" with 50 sxs cement blend with 50# hulls to Max. P.S.I. 100#. Close in P.S.I. 0#. Plug complete.

Remarks:

Condition of casing(in hole): GOOD BAD Anhy.plug: YES NO
Bottom plug(in place): YES , CALC , NO Dakota plug: YES , NO
Plugged through TUBING , CASING . Elevation: GL

I did [X] / did not [] observe the plugging.

Carl Goodrow
(agent)

DATE 9-6-95

INV. NO. 43404