

4-032309

6-18

TO: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
130 SOUTH MARKET, SUITE 2078  
WICHITA, KANSAS 67202

API Number: 15-147-20,162 -00-00

RECEIVED

JUL 07 1998

C SE SW /4 SEC. 15, 01, 18 W  
660 feet from S section line  
3300 feet from E section line

Operator license# 5352

CONSERVATION DIVISION  
Wichita, Kansas

Lease: Oneill Well # E-1

Operator: Baird Oil Company, Inc.

County: Phillips 114.24

Address: Box 428  
Logan, Kansas 67646

Well total depth 3515 feet  
Conductor Pipe: 0 inch @ 0 feet  
Surface pipe 8 5/8 Inch @ 231 feet

Aband. oil well , Gas well \_\_\_\_\_, Input well \_\_\_\_\_, SWD \_\_\_\_\_, D & A \_\_\_\_\_

Plugging contractor: Allied Cement Company License# -

Address: Russell, Kansas 67665

Company to plug at: Hour: P.M. Day: 18 Month: June Year: 1998

Plugging proposal received from: Jim Baird

Company: Baird Oil Company, Inc. Phone: -

Were: Order 200 sxs 60/40 pozmix - 10% gel - 500# hulls.

Plugging Proposal Received by: Carl Goodrow

Plugging operations attended by agent? All , Part [ ], None [ ]

Completed: Hour: 12:00 P.M., Day: 18 Month: June Year: 1998

Actual plugging report: 8 5/8" set at 231' w/150 sxs.cwc. 4 1/2" set at 3497' w/235 sxs.  
Prod.perfs 3316' - 3358'. Squeezed at 1760' w/175 sxs. Critical area control shots at  
1100' - 1700'. Squeezed 4 1/2" with 175 sxs cement blend with 500# hulls to Max. P.S.I.  
100#. Close in P.S.I. 0#. Squeezed 8 5/8" with 25 sxs cement blend to Max. P.S.I. 150#.  
Plug complete.

Remarks: Anhydrite 1673'. Elevation 2080' KB.

Condition of casing(in hole): GOOD \_\_\_\_\_ BAD \_\_\_\_\_ Anhy.plug: YES  NO \_\_\_\_\_

Bottom plug(in place): YES \_\_\_\_\_, CALC \_\_\_\_\_, NO \_\_\_\_\_ Dakota plug: YES , NO \_\_\_\_\_

Plugged through TUBING \_\_\_\_\_, CASING \_\_\_\_\_ Elevation: \_\_\_\_\_ GL

I did  / did not [ ] observe the plugging.

Carl Goodrow  
(agent)

INVOICED

DATE

7-13-98

INV. NO.

50896