

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-163-30025-00-00
Spot: SESWNW Sec/Twnshp/Rge: 6-10S-17W
2970 feet from S Section Line, 4290 feet from E Section Line
Lease Name: POSTGATE Well #: 3
County: ROOKS Total Vertical Depth: 3580 feet

Operator License No.: 8133
Op Name: HAMMERSCHMIDT, WILLIAM E
Address: 904 S SECTION LINE
PLAINVILLE, KS 67663

PROD Size: 4.5 feet: 3578 w/150 sxs cmt
SURF Size: 7 feet: 195 w/100 sxs cmt

35
#116

Well Type: OIL UIC Docket No: _____ Date/Time to Plug: 03/10/2004 9:00 AM

Plug Co. License No.: 99998 Plug Co. Name: COMPANY TOOLS

Proposal Rcvd. from: BILL HAMMERSCHMIDT Company: HAMMERSCHMIDT, WILLIAM E. Phone: (785) 434-2403

Proposed Plugging Method: Ordered out 280 sxs 60/40 pozmix - 10% gel - 500# hulls.
Casing leak 1000' - Cedar Hills Sand.
Fluid level 400'.
1969 - squeezed 900' w/150 sxs.

Plugging Proposal Received By: RICHARD WILLIAMS

Witness Type: COMPLETE (100%)

Date/Time Plugging Completed: 03/10/2004 11:30 AM

KCC Agent: RICHARD WILLIAMS

Actual Plugging Report:

Perfs:

Ran tubing to 1800'.
Allied pumped 100 sxs 60/40 pozmix - 10% gel with 300# hulls - no circulation.
Pulled tubing to 1360'.
Allied pumped 100 sxs cement with 200# hulls - cement circulated.
P.T.O.H. Squeezed with 30 sxs cement.
Max. P.S.I. 400#. S.I.P. 200#.
Hooked up to backside 7". Allied pumped 50 sxs cement.
Max. P.S.I. 100#. S.I.P. 100#.

RECEIVED
MAR 15 2004
KCC WICHITA

Remarks: ALLIED CEMENTING COMPANY.

Plugged through: TBG

District: 04

Signed

Richard Williams

(TECHNICIAN)

INVOICED

DATE

3-17-04

INV. NO.

2004061291

Form CP-2/3

MAR 12 2004

S-T-R-6-10S-17W
 SPOT SE SW NW
 CO. ROOKS (Ks)
 ELEV. 2121 KB

Map No. _____
 OPER. HAMMONDS OIL CO. - Plainville, Ks.
 WELL #3 POSEGATE
 CONTR Chem-Tech
 FIELD Plainville (Lans Oil)
 P. P 25 BOPD & tr wtr, Lans 3435-3524 (OA)

(KB Spl's:)

1395 f 726
 3045 - 924
 3264 - 1143
 3285 - 1164
 3306 - 1185
 3531 - 1410
 3557 - 1436
 3580 - 1456

No DST's or Cores, RTD 3580, No OH Log, 4 1/2" @3578' w/
 150 Sx., Great Guns Perf Log, Pf 6/3435-38, 6/3462-65, Tor
 10/3478-83, 2/3508-09, 6/3521-24 (Lans), 14,000 Total
 Acid, No \$, POP, Rec 1d, Co P 25 BOPD / tr wtr, Lans
 3435-3524 (OA) - COMPLETED on 7-6-65

MISCELL DATA
 GEOL. Jack Cole ELEV 2116 GR. SPUD. DATE 5-22-65
 FTG 2118 DF DRIG COMP
 SUPPT FR by DATA 6-18-65
 CSG 7" @195 w/100 sx. 4" @3578 w/150 sx. COMP by " 7-8-65