Rev. 12/14/82 FORM CP-1

STATE OF KANSAS STATE CORPORATION COMMISSION CONSERVATION DIVISION 200 Colorado Derby Building Wichita, Kansas 67202

WELL PLUGGING APPLICATION FORM File One Copy

API NUMBER 15-153-20653 ~ (of this well) (This must be listed; if no API# was issued, please	note drilling completion date.
LEASE OPERATOR Viking Resources	OPERATORS LICENSE NO. 5011
ADDRESS 217 E. William, Wichita, Kansas 67202	PHONE # (316)262-2502
LEASE (FARM NAME) Wicke	WELL NO. 2
WELL LOCATION C E/2 SE NW SEC. 16	_TWP1 RGE32 (%)or(W)
COUNTY Rawlins TOTAL DEPTH 41	170' FIELD NAME
check one: OIL WELLGAS WELLINPUT WELLSWD WELD	LD&A_X
IS WELL LOG ATTACHED TO THIS APPLICATION AS REQUIRED? YOU (If not, explain) ACO-1 to be filed by operator	es IS ACO-1 FILED? NO
DATE AND HOUR PLUGGING IS DESIRED TO BEGIN as soon as	possible
PLUGGING OF THIS WELL WILL BE DONE IN ACCORDANCE WITH K. REGULATIONS OF THE STATE CORPORATION COMMISSION. NAME OF COMPANY REPRESENTATIVE AUTHORIZED TO BE IN CHARCE Dan Jones ADDRESS Box 1586,	
PHONE #_(316)792-2424	,
PLUGGING CONTRACTOR White & Ellis Drilling, Inc.	LICENSE NO. 5420
ADDRESS 401 E. Douglas, Suite 500, Wichita, Ksp	IONE # (316)263-1102
67202 INVOICE COVERING ASSESSMENT FOR PLUGGING THIS WELL SHOUL	
NAME Viking Resources	•
ADDRESS 217 E. William, Wichita, Kansas 67202 PH	ONE # (316)262-2502
AND PAYMENT WILL BE GUARANTEED BY APPLICANT OR ACTING AG	ENT.
SIGNED:	e S view
STATE CORPORATION COMMISSION	plicant of Acting Agent)
APR - 3 1986 APR - 3 1986 CONSERVATION DIVISION	4-2-86

Wichita, Kansas

NOTICE OF INTENTION, TO DRILL

1.20 Starting Date	',o	£ 12 c/ 4 f 0 2 c c c		isas Lasta massas assas	_	CARD MUST BE SIGI
•			OF INTENT	J I	.1.	
Starting Date		•	(see rules on reve	rse side) - ^		•
·/•			A	PI Number 15	153 20	653-00-
OPERATOR: Lices	nse # 5011		C	EF SE NW	Sec. 16. Two. 1	s, Rg32 X
Name		Resources				Ft. from South Line of S
Address	. 	William	*********			Ft. from East Line of S
City/State/Zip		i, KS 67202-40	105	(Note: 1,	scate well on Section Pl	at on reverse side)
Contact Person			••••			,
Phone		2-2502				3.30
CONTRACTOR: 1	License # 542U		C	CountyRAY	lins	
		rilling, Inc.		ease Name	Wicke	Well #2
						295.0.estfeet
Well Drilled For:				omestic well with		yes \(\frac{\fin}}}}}}{\frac}}}}}}}{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\fir}}}}}}}}}{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac}}}}}}}{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac}}}}}}{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac}}}}}}{
					hin one mile:	yes \(\sum_{\text{\tin}\exititt{\texi{\text{\texi}}\tint{\text{\text{\texi}\titt{\text{\text{\text{\texit{\text{\texi\texi{\texi{\texi}}\\ \texitit{\text{\texi{\texi{\texi{\texi{\texi{\texi{\texi{\tex
	•			urface pipe by Ali		1 X 2
	•	Wildcat Ca			fresh water	
H OWWO; old well					usable water	
•		• • • • • • • • • • • • • • • • • • • •			ed to be set	
			P	rojected Total De	oth	4Z 0 0
		tal Depth			ase Kansas Cit	:y
r certify that wen	wiii compiy with K	C.S.A. 55-101, et seq.,	, plus eventually I	Mugging hole to k	CC specifications.	,
12 Febru	erv 1986	be done immediately	v upon setting pro	duction casing.	0	. Ectiff
Date Commission	manure :	of Operator or Agen	#		\dots Title \dots $\Omega \Omega$	GLITTOL
Occas	Atelie.		Plug	ging propos	1 9.	,
				3/26	186 IND	•
0 '				FABOVÉ IS E	& A 112	*
This plugging prop	osał will be reviewe			FABOVÉ IS E	& A 112	surface casing (call 7 a.
0 '		ed and approved or re		FABOVÉ IS E	& A 112	surface casing (call 7 a.
This plugging propo 5 p.m. workdays),		ed and approved or re	vised at the time th	FABOVÉ IS E pedistricroffice is a	& A Was alled prior to setting	
This plugging proposition of p.m. workdays).	drite approx.	ed and approved or re 2760	evised at the time th	F ABOVÉ IS E redistrict office is a 25	alled prior to setting	, 4% gel, 3% CC
this plugging proposes p.m. workdays). Ist plug (a Anhy 2nd plug (a Dako	drite approx. ta approx. 22	ed and approved or re 2.760 2750 feet depth v	with 20	F ABOVÉ 18-1: redistrict office is a 25 100	atled prior to setting	, 4% gel, 3% CC
This plugging proposes p.m. workdays). Ist plug (a	drite approx. ta approx. 22 Surface 280'	2760 2760 2750 feet depth v 50240 feet depth v	with 20 with 100 with 40	F ABOVÉ 18-1: redistrict office is a 25 100	alled prior to setting oxs of .60/40 poz exs of .!!	surface casing (call 7 a.
This plugging prop 5 p.m. workdays). Ist plug (a. Anhy 2nd plug (a. Dako 3rd plug (a. Base 40	drite approx. ta approx. 22 Surface 280'	2760 2750 feet depth v 50240 feet depth v 520 feet depth v 40 feet depth v	with 20 with 100 with 40 with 16	F ABOVÉ 18-1: redistrict office is a 25 100 40	alled prior to setting oxs of 60/40 poz exs of	, 4% gel, 3% CC
This plugging prop 5 p.m. workdays). Ise plug (a. Anhy 2nd plug (a. Dako 3rd plug (a. Base 40	drite approx. ta approx. 22 Surface 280'	2760 2750 feet depth v 50240 feet depth v 520 feet depth v 40 feet depth v	with 20 with 100 with 40 with 16	F ABOVÉ IS E redistrict office is a 25 100 40	alled prior to setting oxs of 60/40 poz exs of oxs of oxs of	, 4% gel, 3% CC
this plugging prop 5 p.m. workdays). Ist plug (a. Anhy 2nd plug (a. Dako 3rd plug (a. Base tth plug (a. 40	drite approx. ta approx. 22 Surface 280'	2760 2760 2750 feet depth v 50240 feet depth v	with 20 with 100 with 40 with 16	F ABOVÉ IS E redistrict office is a 25 100 40	alled prior to setting oxs of 60/40 poz exs of oxs of oxs of	, 4% gel, 3% CC
This plugging proposes p.m. workdays). Ist plug (a. Anhy 2nd plug (a. Base 3rd plug (a. 40. 5th plug (a. (2) Rathole with	drite approx. ta approx. 22 Surface 280'	2760 2750 feet depth v 50240 feet depth v 320 feet depth v 40 feet depth v feet depth v	with 20 with 100 with	F ABOVÉ IS 1. 25 100 10	alled prior to setting axs of .60/40 poz axs of axs of axs of by Mousehole with	, 4% gel, 3% CC
This plugging proposes p.m. workdays). Ist plug (a	drite approx. 22 Surface 280'	2760 2750 feet depth v 50240 feet depth v 50240 feet depth v 40 feet depth v feet depth v	with 20 with 100 with 100 with 100 with 10	F ABOVE 1S 1: de district office is a 25 100 40 10 3/24/86 ad the amount of c	alled prior to setting axs of .60/40 poz axs of axs of axs of by Mousehole with conent to be used is n	, 4% gel, 3% CC
This plugging proposes p.m. workdays). Ist plug (a	drite approx. 22 Surface 280'	2760 2750 feet depth v 50240 feet depth v 	with 20 with 100 plug placement ar or production cas	F ABOVE 1S 1: 25 100 40 10 3/24/86 ad the amount of cing is comented i	alled prior to setting axs of .60/40 poz axs of axs of axs of by Mousehole with conent to be used is n	, 4% gel, 3% CC
This plugging proposes p.m. workdays). Ist plug (aAnhy 2nd plug (aBase) Ith plug (aBase) Ith plug (a(2) Rathole with	drite approx. 22 Surface 280'	2760 2750 feet depth v 50240 feet depth v 	with 20 with 100 with 100 with 100 with 10	F ABOVE 1S 1: 25 100 40 10 3/24/86 ad the amount of cing is comented i	alled prior to setting axs of .60/40 poz axs of axs of axs of by Mousehole with conent to be used is n	, 4% gel, 3% CC
This plugging proposes p.m. workdays). 1st plug (a	drite approx. 22 Surface 280' 15 between operator a trict office after we	2760 2750 feet depth v 50240 feet depth v 50240 feet depth v 40 feet depth v feet depth v feet depth v common sas	with 20 with 100 with 100 with 100 with 100 with 100 with 100 plug placement ar or production cas Il 7 a.m. to 5 p.m.	F ABOVE 1S 1: 25 100 40 10 3/24/86 ad the amount of cing is comented i	alled prior to setting axs of .60/40 poz axs of axs of axs of by Mousehole with conent to be used is n	, 4% gel, 3% CC
This plugging proposes p.m. workdays). Ist plug (a. Anhy 2nd plug (a. Base 3rd plug (a. Base 40. 5th plug (a. (2) Rathole with NOTT: Agreement Important: Call district office use (a. API # 15	drite approx. 22 Surface 280' 5 between operator a trict office after we only:	2760 2750 feet depth v 50240 feet depth v 50240 feet depth v 60 feet depth v	with 20 with 100 plug placement ar or production cas II 7 a.m. to 5 p.m.	F ABOVE 1S Energia district office is a second of the amount of coing is comented in workdays)	alled prior to setting oxs of	ccessary prior to plugg
This plugging proposes p.m. workdays). Ist plug (a. Anhy 2nd plug (a. Base 3rd plug (a. Base 40. 5th plug (a. (2) Rathole with NOTT: Agreement Important: Call district office use (a. API # 15	drite approx. 22 Surface 280' 5 between operator a trict office after we only:	2760 2750 feet depth v 50240 feet depth v 50240 feet depth v 60 feet depth v	with 20 with 100 plug placement ar or production cas II 7 a.m. to 5 p.m.	F ABOVE 1S Energia district office is a second of the amount of coing is comented in workdays)	alled prior to setting oxs of	ccessary prior to plugg
This plugging proposes p.m. workdays). Ist plug (aAnhy 2nd plug (aBase) Ith plug (aBase) Ith plug (a(2). Rathole with	drite approx. 22 Surface 280' 15 between operator a trict office after we only: 23-24 or 2 surface	2760 2750 feet depth v 50240 feet depth v 60 feet depth v	with 20 with 700 with 60 with 60 with 60 with 100 plug placement ar or production cas Il 7 a.m. to 5 p.m.	F ABOVE 1S Energistic testing is commented in workdays)	alled prior to setting axs of .60/40 poz axs of axs of axs of by Mousehole with conent to be used is not. REC	CCESSARY PRIOR to plugg
This plugging proposes p.m. workdays). Ist plug (aAnhy 2nd plug (aBase Base th plug (a(2)) Rathole with	drite approx. 22 Surface 280' 15 between operator a trict office after we only: 23-24 or 2 surface	2760 2750 feet depth v 50240 feet depth v 60 feet depth v	with 20 with 700 with 60 with 60 with 60 with 100 plug placement ar or production cas Il 7 a.m. to 5 p.m.	F ABOVE 1S Energistic testing is commented in workdays)	alled prior to setting axs of .60/40 poz axs of axs of axs of by Mousehole with conent to be used is not. REC	CCESSARY PRIOR to plugg
This plugging prope 5 p.m. workdays). Ist plug (a Anhy 2nd plug (a Dako 3rd plug (a Base 40 5th plug (a	drite approx. 21 2 2 2 3 2 3 2 4 2 4 2 4 2 4 2 4 2 4 2 4	2760 2750 feet depth v 50240 feet depth v 50240 feet depth v 60 feet depth v 60 feet depth v 60 sxs and district office on ell is either plugged (Cal	with 20 with 100 with 16 with 16 with 16 with 16 plug placement ar or production cas Il 7 a.m. to 5 p.m.	F ABOVE 1S Established is controlled in the amount of controlled in workdays) Legal	alled prior to setting oxs of .60/40 poz exs of oxs of oxs of oxs of oxs of oxs of EXEC	FIVED S, R
This plugging prope 5 p.m. workdays). Ist plug (a Anhy 2nd plug (a Dako 3rd plug (a Base 40 5th plug (a	drite approx. 21 2 2 2 3 2 3 2 4 2 4 2 4 2 4 2 4 2 4 2 4	2760 2750 feet depth v 50240 feet depth v 60 feet depth v	with 20 with 100 with 16 with 16 with 16 with 16 plug placement ar or production cas Il 7 a.m. to 5 p.m.	F ABOVE 1S Energia de district office is of 25 and 40 and the amount of coing is comented in workdays) Legal	alled prior to setting axs of .60/40 poz axs of axs of axs of by Mousehole with conent to be used is not. REC	ccessary prior to plugg EIVED s, R KDHE 19 1 7 1986 19

CONSERVATION DIVISION
Wichita, Kansas