

15-039-19003-00-01

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: ~~15-039-19003-00-00~~
Spot: CSESENW Sec/Twnshp/Rge: 11-1S-27W
2970 feet from S Section Line, 2970 feet from E Section Line
Lease/Unit Name: WARNER UNIT Well Number: 301 W
County: DECATUR Total Vertical Depth: 3381 feet

Operator License No.: 31660 Conductor Pipe: Size feet: \$109.88
Op Name: ENERGY SEARCH OPERATING COMPAN Surface Casing: Size 8.625 feet: 280 225 sx cmt
Address: P.O. BOX 31697 Production: Size 5.5 feet: 3380 200 sx cmt
AURORA, CO 80041 Liner: Size feet:

Well Type: EOR UIC Docket No: E12401.8 Date/Time to Plug: 02/21/2001 9:00 AM

Plug Co. License No.: 31660 Plug Co. Name: ENERGY SEARCH OPERATING COMPANY

Proposal Rcvd. from: RAY DORTHY Company: ENERGY SEARCH OPERATING CO Phone: (303) 344-2067

Proposed Plugging Method: Ordered 225 sxs 60/40 pozmix - 10% gel - 500# hulls.

Plugging Proposal Received By: CARL GOODROW Witness Type: Plugging Operations 100% Witnessed (Complete)
Date/Time Plugging Completed: 02/21/2001 10:15 AM KCC Agent: CARL GOODROW

Actual Plugging Report:

8 5/8" set at 280' w/225 sxs cwc. 5 1/2" set at 3380' w/200 sxs.
Prod. Perfs 3159' - 3350'.
PBTD 3365'. Exempt area.
Squeezed 5 1/2" with 175 sxs cement blend with 500# hulls mixed into Max. P.S.I. 100#. Held.
Squeezed 8 5/8" with 50 sxs cement blend to Max. P.S.I. 100#. Held.
Plug complete.

INVOICED
DATE 03-08-2001
INV. NO. 200061459

RECEIVED
STATE CORPORATION COMMISSION
MAR 6 2001
CONSERVATION DIVISION
Wichita, Kansas

Remarks: ALLIED CEMENTING COMPANY. FORMERLY KNOWN AS THE REDMAN #1.

Plugged through: CSG

District: 04

Signed Carl Goodrow
(TECHNICIAN)

FEB 27 2001

D G HANSEN

#1 REDMAN

11-1-27W
SE SE NW

Contr. C-G DRLG

DECATUR County

E 2502RB Comm. 2-18-57

Comp. 5-3-57

IP 38 BOPD/LANS

PHY POT

Tops	Depth	Datum
ANH	1861	641
HEEB	3118	-616
LANS	3160	-658
B/KC	3272	-770
TD	3400	-898

Casing

8" 280

5" 3389

DST 3163-85/41", 35' O SPKD M, BHP 890#

DST 3179-3225/1 1/2 HR, 45' G, 20' O, 175' H OCM, BHP 120#

DST 3219-65/1 HR, 50' SL OCM, BHP 770#

DST 3326-57/1 HR, 50' SL OCM, BHP 210#

PERF 3240-50, WTR: SSO: PB 3230: PERF

3188-95, 3200-06: ACID 2000: 8 BOPH

WARNER POOL

INDEPENDENT OIL & GAS SERVICE
WICHITA, KANSAS