TO:	API number: 15-153-20,801 -00
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING	<u>NW NE NE</u> /4 SEC. 36 , 01 S, 32 W
200 COLORADO DERBY BUILDING	4950 feet from S section line
WICHITA, KANSAS 67202	990 feet from E section line
Operator license#_5131_	Lease_Wicke well #_1
Operator: Thunderbird Drilling Inc.	County Rawlins Well total depth 4080 feet
Address: P.O. Box 780407 Wichita, Kansas 67278 (316)685-1441	Well total depth 4080 feet
Wichita, Kansas 67278	Conductor Pipe: inch @ feet
(316) 685-1441	Surface pipe 8 5/8 inch @ 222 feet
Aband. oil well, Gas well, Inpu	ıt well, SWD, D & A <u>X</u>
Plugging contractor: White & Ellis	License#
Address:	
Company to plug at: Hour: PM Day:	12 Month: July Year: 1994
Plugging proposal received from: <u>Judy</u>	
Company: White & Ellis Drlg.	phone:
Were: Spot plugs through drill pipe w/	heavy mud between all plugs.
1st plug @ 2660 feet with 25 sacks	Rat hole: 15 sacks
2nd plug @ 2020 feet " 100 "	
3rd plug @ <u>270</u> feet " 40 "	
4th plug @ 40 feet " 10 "	with 8 5/8" wiper plug
Plugging Proposal Received by: Marvin L. Miller	
Plugging operations attended by agent?	All[], Part[], None[X]
Completed: Hour: 6:30 PM , Day: 12 , Mor	All[], Part[], None[X] oth: July , Year; 1998 CONPORATION COMM
Actual plugging report: Hole reported	d plugged as above.
Order 190 sx 60/40 pozmix w/ 6% gel and	
	CONSERVATION
	CONSERVATION DIVISION Wichita, Kansas
Remarks: Elevation: 2868, Anhydrite: 2646- Bottom plug (in place): Yes X,	- <u>2680</u> feet, Anhydrite plug: <u>2660</u>
Did not penetrate Arbuckle, cemented by	
I did 0 (Cit hot[X] observe the p	lugging. Mawin L. Miller
7-27-94	Marvin L. Miller P.I.R.T.II
40899 SEP 2 8 1994	(agent) Form CP-2/3