4-<u>032173</u>

TO:	API Number: 15-153-20, 121-06-00
STATE CORPORATION COMMISSION 9-6	
CONSERVATION DIVISION - PLUGGING	<u>SW NW</u> /4 SEC. <u>14</u> , <u>01</u> , <u>34 W</u>
130 SOUTH MARKET, SUITE 2078	feet from S section line
WICHITA, KANSAS 67202	4620 feet from E section line
Operator license#_5552_	Lease:Fikan "B" Well #3
Operator: Gore Oil Company	County: Rawlins 140.40
Address: P.O. Box 2757	Well total depth 4320 fe
Wichita, Kansas 67201-2757	Conductor Pipe: 0 inch @ 0 fe Surface pipe 8 5/8 Inch @ 330 fe
Aband. oil well_x_, Gas well, Input well_	, SWD, D & A
Plugging contractor: Halliburton Services	License#
Address: Hays, Kansas 67601	
Company to plug at: Hour: P.M. Day: 6	Month: September Year: 1996
Plugging proposal received from: Lester Be	tts
Company: Gore Oil Company	Phone:
Were: <u>Order 400 sxs 60/40 pozmix - 10% g</u>	3 8
WCIC. OIGHT TOU BAS 00/40 DOZMIA - 10% ye	51 - JUUT 114115.
	~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~
	Dim.
	\$ 5°
Plugging Proposal Received by: Carl Goods	COW COW
Plugging operations attended by agent? All[]	K], Part[], None[] 10-2-9
Completed: Hour: 1:15 P.M., Day: 6, Month	: <u>September</u> , Year: 1996
Actual plugging report: 8 5/8" set at 330' cwo	c with 225 sxs. 5 1/2" set at 4319' with 1
<pre>sxs. D.V. set at 3058' cwc with 200 sxs cwc. 500# hulls mixed into Max. P.S.I. 300#. Held.</pre>	Squeezed 5 1/2" w/350 sxs cement blend wi
Max. P.S.I. 250#. Held. Plug complete.	Squeezed o 5/6" with 50 sxs cement blend
Remarks: GOOD BAI	Anher niver VEC W MA
Bottom plug(in place): YES, CALC,	NO Dakota plug. VEG W NO
Plugged through TUBING, CASING	Elevation:
I did[x] / did not[] observe the plugging	Carl Goodwar
INVOICED	(agent) Form CP-2/3
ATE 10-3-96 VV. NO. 46649	" "
W. NO. 46647	