

6 031405

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 153-05284-00-01

C. SW SW, SEC. 10, T 1 S, R 34 W&E

660 feet from S section line

4620 feet from E section line  
Cahoj Unit 28

Lease Name C. G. Kisilowski # 5

County Rawlins 140.04

Well Total Depth 4309 feet

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 328

TECHNICIAN'S PLUGGING REPORT

Operator License # 3911

Operator: Rama Operating Co. Inc.

Name & Address Box 159

Stafford, Ks. 67578

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well xx SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Allied Cement Co. License Number \_\_\_\_\_

Address Russell, Ks.

Company to plug at: Hour: PM Day: 22 Month: August Year: 19 90

Plugging proposal received from Lloyd Frederick

(company name) Rama (phone) \_\_\_\_\_

were: 8 5/8 set at 328 w/250 sks cwc. 5 1/2 set at 4310 w/150 sks.

Perf 4128 - 78. Ordered 300 sks 65/35 poz 8% gel. Allied Cement Co

LaRue Water Trucks.

Plugging Proposal Received by Carl Goodrow  
(TECHNICIAN)

Plugging Operations attended by Agent?: All xx Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 5:15PM Day: 22 Month: August Year: 19 90

ACTUAL PLUGGING REPORT Mix and pump down tubing to circulate cement to surface.

Lay down tubing, tie onto 5 1/2 casing, sq w/total of 225 sks cement blend to max psi 300 lbs.

Close in psi 300 lbs. Sq backside w/100 sks w/100 lbs hulls. To max psi 400 lbs. Close in psi 200 lbs. Plug complete.

RECEIVED  
STATE CORPORATION COMMISSION

OCT 3 1990

CONSERVATION DIVISION  
Wichita, Kansas

Remarks: \_\_\_\_\_  
(If additional description is necessary, use BACK of this form.)

INVOICED

DATE 10-8-90

INV. NO. 29566

*Gib.S.*

Signed Carl Goodrow  
(TECHNICIAN)  
Carl Goodrow

6 031405

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 153-05284-00-01

C SW SW, SEC. 10, T 1 S, R 34 W&E

TECHNICIAN'S PLUGGING REPORT

Operator License # 3911

Operator: Rama Operating Co. Inc.

Name &

Address Box 159

Stafford, Ks. 67578

660 feet from S section line

4620 feet from E section line  
Cahoj Unit 28

Lease Name C. G. Kisling # 5

County Rawlins

Well Total Depth 4309 feet

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 328

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well xx SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_ Right

Plugging Contractor Allied Cement Co. License Number \_\_\_\_\_

Address Russell, Ks.

Company to plug at: Hour: PM Day: 22 Month: August Year: 19 90

Plugging proposal received from Lloyd Frederick

(company name) Rama (phone) \_\_\_\_\_

were: 8 5/8 set at 328 w/250 sks cwc. 5 1/2 set at 4310 w/150 sks.

Perf 4128 - 78. Ordered 300 sks 65/35 poz 8% gel. Allied Cement Co

LaRue Water Trucks.

DK - Perf?

Plugging Proposal Received by Carl Goodrow  
(TECHNICIAN)

Plugging Operations attended by Agent?: All xx Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 5:15PM Day: 22 Month: August Year: 19 90

ACTUAL PLUGGING REPORT Mix and pump down tubing to circulate cement to surface.

Lay down tubing, tie onto 5 1/2 casing, sq w/total of 225 sks cement blend to max psi 300 lbs.

Close in psi 300 lbs. Sq backside w/100 sks w/100 lbs hulls. To max psi 400 lbs. Close in psi 200 lbs. Plug complete.

The 5 1/2 casing was full of holes across the Cedar Hills & Dakota Lms. J.H.

Remarks: \_\_\_\_\_  
(If additional description is necessary, use BACK of this form.)

I (did / ~~did not~~) observe this plugging.

J.G.S

Signed Carl Goodrow  
(TECHNICIAN)  
Carl Goodrow