

TO:  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
130 SOUTH MARKET, SUITE 2078  
WICHITA, KANSAS 67202

API Well Number: 15-153-20226-00-00  
Spot: SWNE Sec/Twnshp/Rge: 1-1S-34W  
3300 feet from S Section Line, 1980 feet from E Section Line  
Lease Name: CAHOJ UNIT Well #: 4-1  
County: RAWLINS Total Vertical Depth: 4210 feet

Operator License No.: 30606  
Op Name: MURFIN DRILLING CO., INC.  
Address: 250 N. WATER, STE 300  
WICHITA, KS 67202

PROD Size: 5.5 feet: 4206 w/125 sxs cmt  
SURF Size: 8.625 feet: 210 w/150 sxs cmt

*136<sup>83</sup>*

Well Type: OIL UIC Docket No: \_\_\_\_\_ Date/Time to Plug: 06/14/2004 9:30 AM  
Plug Co. License No.: 30606 Plug Co. Name: MURFIN DRILLING CO., INC.  
Proposal Rcvd. from: JOHN TURNER Company: MURFIN DRILLING CO., INC. Phone: (785) 443-1031

Proposed Plugging Method: Ordered 320 sxs Midcon II Cement and 1000# hulls.  
Plug through tubing.

Plugging Proposal Received By: HERB DEINES Witness Type: COMPLETE (100%)  
Date/Time Plugging Completed: 06/14/2004 12:00 PM KCC Agent: DARREL DIPMAN

Actual Plugging Report:

8 5/8" surface casing set at 210' w/150 sxs cement.  
5 1/2" production casing set at 4206' w/125 sxs cement.  
PBSD 4175'.  
Ran tubing to 2500' - pumped 75 sxs cement with 600# hulls.  
Pulled tubing to 1200' - pumped 90 sxs cement with 400# hulls. Cement to surface.  
Pulled tubing to surface - pumped 45 sxs cement.  
Max. P.S.I. 400#. S.I.P. 200#.  
Connected to 8 5/8" surface casing - pumped 10 sxs cement.  
Max. P.S.I. 200#. S.I.P. 200#.

Perfs:

Top	Bot	Thru	Comments
4108	4111		

RECEIVED  
JUN 24 2004  
KCC WICHITA

Remarks: LEASE FORMERLY KNOWN AS PETERSON A-1. SWIFT SERVICES, INC.-TICKET #6928.

Plugged through: TBG

District: 04

Signed Darrel Dipman  
(TECHNICIAN)

INVOICED

DATE 6-24-04  
REF. NO. 2004061777

JUN 17 2004

1-1-34W  
C SW NE

PICKRELL DRUG. CO. #1 PETERSON "A"

705 4TH NATL. BK. BLDG., WICHITA, KS.  
CONTR CO. TOOLS CITY RAWLINS

SEOL FIELD CAHOJ NE EXT

3012 KB C-15/75 CARD ISSUED 2/5/76 P 50 BOPD N/W  
LKC 4108-11, GR 37°

API 15-153-20, 226

LOG	TYPE	DEPTH	DATUM
ANH		2854	+ 158
HEEB		3856	- 846
LANS		3908	- 826
DRUM		4065	-1053
SIARS		4124	-1112
BKC		4179	-1167
LTD		4205	-1194
RID		4210	-1198

E 5/8" 210/150SX, 5 1/2" 4206  
 DST (1) 3914-75/30-30-10, 55'M, ISIP 752#  
 NO FSIP, FP 81-104#  
 DST (2) 3979-4000/30-30-10, 10'M, ISIP  
 46#, NO FSIP, FP 46-46#  
 DST (3) 4014-4090/30-30-10, 3'M, ISIP 30#  
 NO FSIP, FP 81-81#  
 DST (4) 4094-4130/30-30-90-50, 1240'GIP,  
 186'CGG, 248'MGO, SIP 1160-1142#, 4P  
 52-104# 115-219#  
 DST (5) 4150-4210/30-30-10, 12'M, ISIP  
 175#, NO FSIP, FP 52-31#  
 VICT - PE 6/4108-4111, A 1000, REC LD &  
 SWB 5.15 BOPD & TR W/1-RS, RE-AC 2000,  
 REC LC & SWB 5.75 BOPD, 1/1W 7HRS, 30P

+	+	+	+
+	+	+	+
+	+	+	+
+	+	+	+

INACTIVE