

To: 6 031177  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

10-14 X 15-039-00537-00-02  
API NUMBER 1-

NE NE SE, SEC. 16, T. 2 S, R. 27 W/E  
2310 feet from S section line  
330 feet from E section line

TECHNICIAN'S PLUGGING REPORT  
Operator License # 5352  
Operator: Baird Oil Co. Inc.  
Name & Address: Box 428  
Logan, Ks. 67646

Lease Name Pelkey Well # 2  
County Decatur 116.71  
Well Total Depth 3591 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 210

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well  D&A \_\_\_\_\_  
Other well as hereinafter indicated D-16,436

Plugging Contractor Halliburton License Number \_\_\_\_\_  
Address Oberlin, Ks.

Company to plug at: Hour: PM Day: 14 Month: Oct Year: 19 88

Plugging proposal received from Jim Baird  
(company name) Baird Oil Co. (phone) \_\_\_\_\_

were: 8 5/8" set at 210' w/200 sks 5 1/2" set at 3588' w/250 sks. 2 3/8" tubing set  
at 2009' w/235 sks. Order 60 sks 60/40 Poz Halliburton PBDT 2000'. Perf 1865' - 1910'.

RECEIVED  
STATE CORPORATION COMMISSION

DEC 29 1988  
12-29-88

Carl Goodnow  
CONSERVATION DIVISION  
(TECHNICAL STAFF)  
Wichita, Kansas

Plugging Proposal Received by \_\_\_\_\_

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 12:30PM Day: 14 Month: Oct Year: 19 88

ACTUAL PLUGGING REPORT Squeezed 8 5/8" w/26 sks cement to max psi 400#.

Held. 5 1/2" has cement to surface. Squeezed 2 3/8" w/34 sks to max psi 1000#. Close in  
psi 950#. Plug complete.

Remarks: \_\_\_\_\_  
(If additional description is necessary, use BACK of this form.)

INVOICED

DATE 1-5-89

INV. NO. 23470

Signed Carl Goodnow  
Carl Goodnow (STAFF)

D

10-14 JAN 06 1989