Give All Information Completely Make Required Affidavit

Form CP-4

WELL PLUGGING RECORD

State Corporation Commission 211 No. Broadway Wichita, Kansas	Decatu	ır	Count	. Sec 11 T	2S Bra	$\frac{28}{\sqrt{E}\sqrt{E}}$ (W)
NORTH		E/CNW%SW%" o	r footage fro	om lines C S	SE SE	982X
NORTH .	Location as "NE/CNW%SW%" or footage from lines C SE SE Lease Owner UNION TEXAS PETROLEUM					
	Lease Name COOK Well No.1					
	Office Address Drawer D, Great Dend, Randa					
	Character of Well (completed as Oil, Gas or Dry Hole) Date well completed 10,15/62 19					
	Date well completed 10/15/62 19					
	Application for plugging filed 10/15/62 19 Application for plugging approved 10/15/62 19					
	Application for plugging approved.					
	Trugging Commenced					
	Plugging completed					
AND DESCRIPTION OF THE PROPERTY AND DESCRIPTION OF THE PROPERY AND DESCRIPTION OF THE PROPERTY AND DESCRIPTION OF THE PROPERTY		ndonment of well L quantitie				
				ast production		19
						ore plugging was com
Locate well correctly on above Section Plat		- Obtained Holli			i its agents beit	ite plugging was com
Name of Conservation Agent who sup	nervised plugging of thi	s well		Eldon	Petty	
Producing formation	rorvised plagging of the	Depth to top	Bottor	m	Total Depth of	WellFee
Show depth and thickness of all wate			Dottor		Total Doptil of	***************************************
-						TACING DECORD
OIL, CAS OR WATER RECOR	D2					CASING RECORD
FORMATION	CONTENT	FROM	то	SIZE	PUT IN	PULLED OUT
				8 5/8"	215'	none
			-			
Set plug @ 550' and rotary mud to 180'.	ment or other plugs we set. cement through set plug No.	ere used, state the h drill pij 2 and cemen	e character of	of same and dept 20 sacks ce gh drill pi	ment. Fil pe with 20	l hole with
n introducing it into the hole. If ce feet for each plug Set plug © 550 and rotary mud to 180. Fill hole with rota	ment or other plugs we set. cement through set plug No.	ere used, state the drill pip 2 and cement of base of	e character of the with of the throught throught throught the cellar,	of same and dept 20 sacks ce gh drill pi	ment. Fil pe with 20	l hole with
n introducing it into the hole. If ce feet for each plug Set plug © 550 and rotary mud to 180. Fill hole with rota	ment or other plugs we set. cement through set plug No.: ry mud to 35	ere used, state the drill pip 2 and cement of base of	e character of the with of the throught throught throught the cellar,	of same and dept 20 sacks ce gh drill pi	ment. Fil pe with 20	l hole with
n introducing it into the hole. If ce feet for each plug Set plug © 550 and rotary mud to 180. Fill hole with rota	ment or other plugs we set. cement through set plug No.: ry mud to 35	ere used, state the drill pip 2 and cement of base of	e character of the with of the throught throught throught the cellar,	of same and dept 20 sacks ce gh drill pi	ment. Fil pe with 20	l hole with
feet for each plug Set plug 550 and rotary mud to 180, Fill hole with rota	ment or other plugs we set. cement through set plug No.: ry mud to 35	ere used, state the drill pip 2 and cement of base of	e character of the with of the throught throught throught the cellar,	of same and dept 20 sacks ce gh drill pi	ment. Fil pe with 20	l hole with
feet for each plug Set plug 550 and rotary mud to 180, Fill hole with rota	ment or other plugs we set. cement through set plug No.: ry mud to 35	ere used, state the drill pip 2 and cement of base of	e character of the with of the throught throught throught the cellar,	of same and dept 20 sacks ce gh drill pi set plug a	ment. Fil pe with 20 nd cap wit	l hole with sacks cement h 10 sacks
feet for each plug Set plug 550 and rotary mud to 180, Fill hole with rota	ment or other plugs we set. cement through set plug No.: ry mud to 35	ere used, state the drill pip 2 and cement of base of	e character of the with of the throught throught throught the cellar,	of same and dept 20 sacks ce gh drill pi set plug a	ment. Fil pe with 20 nd cap wit	l hole with sacks cement h 10 sacks
n introducing it into the hole. If ce feet for each plug Set plug © 550 and rotary mud to 180. Fill hole with rota	ment or other plugs we set. cement through set plug No.: ry mud to 35	ere used, state the drill pip 2 and cement of base of	e character of the with of the throught throught throught the cellar,	of same and dept 20 sacks ce gh drill pi	ment. Fil pe with 20 nd cap wit	l hole with sacks cement h 10 sacks
feet for each plug Set plug 550 and rotary mud to 180, Fill hole with rota	ment or other plugs we set. cement through set plug No.: ry mud to 35	ere used, state the drill pip 2 and cement of base of	e character of the with of the throught throught throught the cellar,	of same and dept 20 sacks ce gh drill pi set plug a	ment. Fil pe with 20 nd cap with RATION COMM	feet of the last o
feet for each plug Set plug 550 and rotary mud to 180, Fill hole with rota	ment or other plugs we set. cement through set plug No.: ry mud to 35	ere used, state the drill pip 2 and cement of base of	e character of the with of the throught throught throught the cellar,	of same and dept 20 sacks ce gh drill pi set plug a	ment. Fill pe with 20 nd cap with conditions communications of 2 2 1962	feet of the latest state of the latest states are states as the latest states are stat
n introducing it into the hole. If ce feet for each plug Set plug © 550 and rotary mud to 180. Fill hole with rota	ment or other plugs we set. cement through set plug No.: ry mud to 35	ere used, state the drill pip 2 and cement of base of	e character of the with of the throught throught throught the cellar,	of same and dept 20 sacks ce gh drill pi set plug a	ment. Fill pe with 20 nd cap with conditions communications of 2 2 1962	feet of the latest state of the latest states are states as the latest states are stat
n introducing it into the hole. If ce feet for each plug Set plug © 550 and rotary mud to 180. Fill hole with rota	ment or other plugs we set. cement through set plug No.: ry mud to 35	ere used, state the drill pip 2 and cement of base of	e character of the with of the throught throught throught the cellar,	of same and dept 20 sacks ce gh drill pi set plug a	ment. Fil pe with 20 nd cap wit ration commi	l hole with sacks cement h 10 sacks
n introducing it into the hole. If ce feet for each plug Set plug © 550 and rotary mud to 180. Fill hole with rota	ment or other plugs we set. cement through set plug No.: ry mud to 35	ere used, state the drill pip 2 and cement of base of	e character of the with of the throught throught throught the cellar,	of same and dept 20 sacks ce gh drill pi set plug a	ment. Fil pe with 20 nd cap wit ration commi	l hole with sacks cement h 10 sacks
n introducing it into the hole. If ce feet for each plug Set plug © 550 and rotary mud to 180. Fill hole with rota	ment or other plugs we set. cement through set plug No.: ry mud to 35	ere used, state the drill pip 2 and cement of base of	e character of the with of the throught throught throught the cellar,	of same and dept 20 sacks ce gh drill pi set plug a	ment. Fil pe with 20 nd cap wit ration commi	feet of the latest the
feet for each plug Set plug 550 and rotary mud to 180, Fill hole with rota	ment or other plugs we set. cement through set plug No.: ry mud to 35	ere used, state the drill pip 2 and cement of base of	e character of the with of the throught throught throught the cellar,	of same and dept 20 sacks ce gh drill pi set plug a	ment. Fil pe with 20 nd cap wit ration commi	l hole with sacks cement h 10 sacks
feet for each plug Set plug 550 and rotary mud to 180, Fill hole with rota	ment or other plugs we set. cement through set plug No.: ry mud to 35	ere used, state the drill pip 2 and cement of base of	e character of the with of the throught throught throught the cellar,	of same and dept 20 sacks ce gh drill pi set plug a	ment. Fil pe with 20 nd cap wit ration commi	l hole with sacks cement h 10 sacks
feet for each plug Set plug 550 and rotary mud to 180, Fill hole with rota	ment or other plugs we set. cement through set plug No. 2 ry mud to 35 completed 5:30	h drill pip 2 and cement of base of AM 10-15-62	e character of the with throughout throughout throughout throughout throughout the cellar,	of same and dept 20 sacks ce gh drill pi set plug a CONSE	ment. Fil pe with 20 nd cap wit ration commi	l hole with sacks cement h 10 sacks
in introducing it into the hole. If ce feet for each plug Set plug © 550' and rotary mud to 180', Fill hole with rota cement. Plugging c	ment or other plugs we set. cement through set plug No. 2 ry mud to 35 completed 5:30 complete	ere used, state the drill pip 2 and cement of base of AM 10-15-62	se character of the with through the cellar, c	of same and dept 20 sacks ce gh drill pi set plug a CONSE K of this sheet) O.	ment. Fil pe with 20 nd cap with 2 2 2 1962 nd cap with 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	l hole with sacks cement h 10 sacks
In introducing it into the hole. If ce feet for each plug Set plug @ 550 and rotary mud to 180. Fill hole with rota cement. Plugging c	ment or other plugs we set. cement through set plug No. 2 ry mud to 35 completed 5:30 complete	ere used, state the drill pip 2 and cement of base of AM 10-15-62	se character of the with through the cellar, c	of same and dept 20 sacks ce gh drill pi set plug a CONSE	ment. Fil pe with 20 nd cap with 2 2 2 1962 nd cap with 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	l hole with sacks cement h 10 sacks
In introducing it into the hole. If ce feet for each plug Set plug @ 550 and rotary mud to 180. Fill hole with rota cement. Plugging c	ment or other plugs we set. cement through set plug No. 2 ry mud to 35 completed 5:30 complete	ere used, state the drill pip 2 and cement of base of AM 10-15-62	se character of the with through the cellar, c	of same and dept 20 sacks ce gh drill pi set plug a CONSE K of this sheet) O.	ment. Fil pe with 20 nd cap with 2 2 2 1962 nd cap with 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	l hole with sacks cement h 10 sacks
In introducing it into the hole. If ce feet for each plug Set plug © 550' and rotary mud to 180', Fill hole with rota cement. Plugging c	ment or other plugs we set. cement through set plug No. 3 ry mud to 35 ompleted 5:30	ere used, state the drill pip 2 and cement of base of AM 10-15-62 WILLIAMSO TON CENTER	se character of the with through the through the cellar, the cellar through through the cellar through the cellar through through the cellar through through the cellar through through the cellar through the cellar through through the cellar through through the cellar through the cellar through through the cellar through through through the cellar through the cellar through through the cellar through through through the cellar through through the cellar t	of same and dept 20 sacks ce gh drill pi set plug a STATE CORP CONSE K of this sheet) O. A 2, KANSAS	ment. Fill pe with 20 nd cap with 20	l hole with sacks cement h 10 sacks
In introducing it into the hole. If ce feet for each plug Set plug © 550' and rotary mud to 180', Fill hole with rota cement. Plugging c	coment or other plugs we set. cement through set plug No. 2 ry mud to 35 completed 5:30 comple	ere used, state the drill pip 2 and cement of base of AM 10-15-62 I description is neces & WILLIAMSO TON CENTER	se character of the with through the through cellar, c	of same and dept 20 sacks ce gh drill pi set plug a STATE CORN CONSE K of this sheet) O. A 2, KANSAS	ment. Fil pe with 20 nd cap wit CT 2 2 1962 CVATION DIV	l hole with sacks cement the losacks cement the losacks cement the losacks sacks sac
In introducing it into the hole. If ce feet for each plug Set plug © 550 and rotary mud to 180 fill hole with rota cement. Plugging c Name of Plugging Contractor Address STATE OF KANSAS Wilson Rains - Part	cment or other plugs we set. cement through set plug No. 2 ry mud to 35 completed 5:30 complet	description is neces WILLIAMS TON CENTER	ssary, use BACON OIL C. WICHIT	of same and dept 20 sacks ce gh drill pi set plug a STATE CORN CONSE K of this sheet) O. A 2, KANSAS owner) or (own	ment. Fil pe with 20 nd cap wit CT 2 2 1962 CVATION DIV	l hole with sacks cement the losacks cement the losacks cement the losacks sacks sa
In introducing it into the hole. If ce feet for each plug Set plug © 550 and rotary mud to 180 fill hole with rota cement. Plugging c Name of Plugging Contractor Address STATE OF KANSAS Wilson Rains - Part well, being first duly sworn on oath,	coment or other plugs we set. cement through set plug No. 2 ry mud to 35 completed 5:30 comple	I description is neces WILLTAMS TON CENTER UNTY OF Lowledge of the	ssary, use BACON OIL CON OIL CON WICHIT	of same and dept 20 sacks ce gh drill pi set plug a STATE CORP CONSE (V) K of this sheet) O. A 2, KANSAS owner) or (owner) and matter	ment. Fil pe with 20 nd cap wit CT 2 2 1962 CVATION DIV	I hole with sacks cement the losacks cement the losacks cement the losacks sacks sa
In introducing it into the hole. If ce feet for each plug Set plug 9 550 and rotary mud to 180. Fill hole with rota cement. Plugging c Name of Plugging Contractor Address STATE OF KANSAS Wilson Rains - Part well, being first duly sworn on oath,	coment or other plugs we set. cement through set plug No. 2 ry mud to 35 completed 5:30 comple	I description is neces WILLTAMS UNTY OF Cowledge of the and correct. So here	ssary, use BACON OIL CON OIL CON OIL CON OIL CON OIL CON CONTRACTOR CONTRACTO	constant constant of same and depth 20 sacks ce gh drill pi set plug a set plug a set plug a constant	ment. Fill pe with 20 nd cap with 20	l hole with sacks cement the losacks cement the losacks cement the losacks sacks sa
In introducing it into the hole. If ce feet for each plug Set plug 9 550 and rotary mud to 180. Fill hole with rota cement. Plugging c Name of Plugging Contractor Address STATE OF KANSAS Wilson Rains - Part well, being first duly sworn on oath,	coment or other plugs we set. cement through set plug No. 2 ry mud to 35 completed 5:30 comple	I description is neces WILLTAMS TON CENTER UNTY OF Lowledge of the	ssary, use BACON OIL CON OIL CON OIL CON OIL CON CONTRACTOR CONTRA	constant constant of same and depth 20 sacks ce gh drill pi set plug a set plug a set plug a constant	ment. Fill pe with 20 nd cap with 20	l hole with sacks cement the losacks cement the losacks cement the losacks sacks sa
In introducing it into the hole. If ce feet for each plug Set plug 9 550 and rotary mud to 180. Fill hole with rota cement. Plugging c Name of Plugging Contractor Address STATE OF KANSAS Wilson Rains - Part well, being first duly sworn on oath,	coment or other plugs we set. cement through set plug No. 2 ry mud to 35 completed 5:30 comple	I description is neces WILLTAMS UNTY OF Cowledge of the and correct. So here	ssary, use BACON OIL CON OIL CON WICHIT	conse and deption of same	ment. Fil pe with 20 nd cap wit CT 2 2 1962 CVATION DIV Chita, Kansa // // // // // // // // //	I hole with sacks cement the log of the above-described and the log of the lo
Name of Plugging Contractor—Address— STATE OF KANSAS Wilson Rains - Part well, being first duly sworn on oath, above-described well as filed and the	coment or other plugs we set. cement through set plug No.: ry mud to 35. completed 5:30 (If additional RAINS 412 UN 412 UN 5. completed 5:30 completed 5:30 All additional RAINS 412 UN 5.	I description is neces WILLTAMS TON CENTER UNTY OF Lowledge of the and correct. So he (Signature)	e character of the with through the through the cellar, cellar, cellar, cellar, cellar, with through the cellar, cellar, cellar, cellar, cellar, cellar, cellar, cellar, with the cellar cellar, cella	conservation of same and depth 20 sacks ceegh drill ping a set plug a set plug a set plug a conservation of this sheet) CONSERVATE CORP. CONSERVATE CORP.	ment. Fill pe with 20 nd cap with 20	I hole with sacks cement the log of the above-described and the log of the sacks
In introducing it into the hole. If ce feet for each plug Set plug © 550 and rotary mud to 180 fill hole with rota cement. Plugging c Name of Plugging Contractor Address STATE OF KANSAS Wilson Rains - Part well, being first duly sworn on oath,	coment or other plugs we set. cement through set plug No.: ry mud to 35. completed 5:30 (If additional RAINS 412 UN 412 UN 5. completed 5:30 completed 5:30 All additional RAINS 412 UN 5.	description is neces WILLIAMS TON CENTER UNTY OF Cowledge of the and correct. So h	ssary, use BACON OIL CON OIL CON WICHIT	CONSE K of this sheet) O. CONSE K of this sheet) O. Rains - Par on Center, er	ment. Fill pe with 20 nd cap with 20	I hole with sacks cement the log of the above-described and the log of the sacks.
In introducing it into the hole. If ce feet for each plug Set plug © 550' and rotary mud to 180', Fill hole with rota cement. Plugging c Address STATE OF KANSAS Wilson Rains - Part well, being first duly sworn on oath, above-described well as filed and the	coment or other plugs we set. cement through set plug No.: ry mud to 35. completed 5:30 (If additional RAINS 412 UN 412 UN 5. completed 5:30 completed 5:30 All additional RAINS 412 UN 5.	I description is neces WILLTAMS TON CENTER UNTY OF Lowledge of the and correct. So he (Signature)	e character of the with through the through the cellar, cellar, cellar, cellar, cellar, with through the cellar, cellar, cellar, cellar, cellar, cellar, cellar, cellar, with the cellar cellar, cella	CONSE K of this sheet) O. CONSE K of this sheet) O. Rains - Par on Center, er	ment. Fill pe with 20 nd cap with 20	I hole with sacks cement the losacks cement the losacks cement the losacks sacks sacks cement the losacks sacks sacks sacks cement the losacks sacks sacks cement the losacks sacks sa

Janet Johnson

My commission expires January 25, 1965