STATE OF KANSAS STATE CORPORATION COMMISSION

Give All Information Completely Ma

WELL PLUGGING RECORD

| Make Required Affidavit | Decatur County. Sec. 30 Twp. 28 Rge. 28W E/W |
|--|---|
| Mail or Deliver Report to | Location as "NE/CNW4SW4" or footage from lines |
| Conservation Division | C NE NE |
| State Corporation Comm. | Lease Owner Bolyard Oil & Gas, Ltd. |
| 245 North Water | Lease Name VOTAPKA Well No. 1 |
| Wichita, KS 67202 | |
| N | Office Address Brooks Towers, Suite 20C, 1020 15th St., Den |
| | Character of Well (Completed as Oil, Gas or Dry Hole) CO. |
| | Dry Hole |
| | Date Well completed 3-20 1977 |
| | Application for plugging filed (Verbally) 3-20 1977 |
| | Application for plugging approved (Verbally) 3-20 1977 |
| | Plugging commenced 3-20 1977 |
| W | Plugging completed 3-20 1977 |
| | |
| | Reason for abandonment of well or producing formation |
| | No commercial quantity of oil or gas encountered |
| | If a producing well is abandoned, date of last production |
| | 19 |
| Lease well correctly on Shove | Was permission obtained from the Conservation Division or |
| Locate well correctly on above Section Plat | its agents before plugging was commenced? Yes |
| Name of Conservation Agent who s | upervised plugging of this well Gilbert Balthazor |
| Producing formation | Depth to top Bottom Total Depth of Well |
| Show depth and thickness of all | |
| bilow dopen and, engointees of all | THE SALE TOTAL SALE TOTAL SALE SALE SALE SALE SALE SALE SALE SA |
| OIL, GAS OR WATER RECORDS | |
| OTH, GAB OR WATER RECORDS | CASING RECORD |
| FORMATION | CONTENT FROM TO SIZE PUT IN PULLED OUT |
| | |
| The state of the s | |
| | |
| | |
| | |
| | |
| Describe in detail the manner | in which the well was plugged, indicating where the mud flui |
| | · · · · · · · · · · · · · · · · · · · |
| was placed and the method or met | hods used in introducing it into the hold. If cement or othe |
| was placed and the method or met plugs were used, state the chara | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from feet to |
| was placed and the method or met | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from feet to |
| was placed and the method or met plugs were used, state the chara feet for each plug | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from feet to |
| was placed and the method or met plugs were used, state the chara | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from feet to |
| was placed and the method or met plugs were used, state the chara feet for each plug | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from feet to set. |
| was placed and the method or met plugs were used, state the chara feet for each plug T.D. 3875' | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from feet to set. th 70 sx. |
| was placed and the method or met plugs were used, state the chara feet for each plug T.D. 3875' Set lost plug at 1300' with 20 | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from feet to set. th 70 sx. sx. |
| was placed and the method or met plugs were used, state the chara feet for each plug T.D. 3875' Set lost plug at 1300' wi | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from feet to set. th 70 sx. sx. |
| was placed and the method or met plugs were used, state the chara feet for each plug T.D. 3875' Set lost plug at 1300' with 20 and plug at 40' with 10 s | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from feet to set. th 70 sx. sx. |
| was placed and the method or met plugs were used, state the chara feet for each plug T.D. 3875' Set lost plug at 1300' with 20 3rd plug at 40' with 10 s Plug was down at 5:00 p.m | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from feet to set. th 70 sx. sx. sx. h. 3-20-77. |
| was placed and the method or met plugs were used, state the chara feet for each plug T.D. 3875' Set lost plug at 1300' with 20 and plug at 40' with 10 s | th 70 sx. sx. 3-20-77. Balthazor. |
| was placed and the method or met plugs were used, state the chara feet for each plug T.D. 3875' Set lost plug at 1300' with 20 3rd plug at 40' with 10 s Plug was down at 5:00 p.m | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from feet to set. th 70 sx. sx. sx. h. 3-20-77. |
| was placed and the method or met plugs were used, state the chara feet for each plug T.D. 3875' Set lost plug at 1300' with 20 3rd plug at 40' with 10 s Plug was down at 5:00 p.m | th 70 sx. sx. 3-20-77. Balthazor. |
| was placed and the method or met plugs were used, state the chara feet for each plug T.D. 3875' Set lost plug at 1300' with 20 3rd plug at 40' with 10 s Plug was down at 5:00 p.m. State Plugger - Gilbert F | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from feet to set. th 70 sx. sx. sx. althazor. |
| was placed and the method or met plugs were used, state the chara feet for each plug T.D. 3875' Set lost plug at 1300' with 20 3rd plug at 300' with 10 s Plug was down at 5:00 p.m. State Plugger - Gilbert F | th 70 sx. sx. 3. 20-77. Balthazor. scription is necessary, use BACK of this sheet) |
| was placed and the method or met plugs were used, state the chara feet for each plug T.D. 3875' Set lost plug at 1300' with 20 3rd plug at 300' with 10 s Plug was down at 5:00 p.m. State Plugger - Gilbert F | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from feet to set. th 70 sx. sx. sx. althazor. |
| was placed and the method or met plugs were used, state the chara feet for each plug T.D. 3875' Set lost plug at 1300' with 20 3rd plug at 300' with 10 s Plug was down at 5:00 p.m. State Plugger - Gilbert F | th 70 sx. sx. 3. 20-77. Balthazor. scription is necessary, use BACK of this sheet) |
| was placed and the method or method plugs were used, state the character feet for each plug T.D. 3875' Set lost plug at 1300' with 20 and plug at 300' with 20 ard plug at 40' with 10 services Plug was down at 5:00 p.m. State Plugger - Gilbert Feet Plugger - Gilbert Feet Plugger - Gilbert Feet Plugging Contractor | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from feet to set. th 70 sx. sx. sx. sx. sx. sx. sx. salthazor. scription is necessary, use BACK of this sheet) Abercrombie Drilling, Inc. |
| was placed and the method or method plugs were used, state the character feet for each plug T.D. 3875' Set lost plug at 1300' with 20 and plug at 300' with 20 ard plug at 40' with 10 services Plug was down at 5:00 p.m. State Plugger - Gilbert Feet Feet Feet Feet Feet Feet Feet F | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from feet to feet feet to feet feet to feet feet to feet feet feet feet feet feet |
| was placed and the method or methology were used, state the character feet for each plug T.D. 3875' Set lost plug at 1300' with 20 and plug at 300' with 20 ard plug at 40' with 10 second plug at 40' with 10 second plug at 40' with 10 second plug at 200 p.m. Plug was down at 5:00 p.m. State Plugger - Gilbert Feet plu | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from feet to set. th 70 sx. sx. sx. sx. sx. sx. sx. scription is necessary, use BACK of this sheet) Abercrombie Drilling, Inc. set. SecTreas. (employee of owner) or (owner or operator) of the above-described |
| was placed and the method or methology were used, state the character feet for each plug T.D. 3875' Set lost plug at 1300' with 20 and plug at 300' with 20 ard plug at 40' with 10 s Plug was down at 5:00 p.m. State Plugger - Gilbert Formula of Plugging Contractor STATE OF Kansas Jack L. Partridge, Aswell, being first duly swom on oath, says: | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from feet to set. th 70 sx. sx. sx. sx. sx. sx. scription is necessary, use BACK of this sheet) Abercrombie Drilling, Inc. set set |
| was placed and the method or methology were used, state the character feet for each plug T.D. 3875' Set lost plug at 1300' with 20 and plug at 300' with 20 ard plug at 40' with 10 s Plug was down at 5:00 p.m. State Plugger - Gilbert Formula of Plugging Contractor STATE OF Kansas Jack L. Partridge, Aswell, being first duly swom on oath, says: | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from feet to set. th 70 sx. |
| was placed and the method or methology were used, state the character feet for each plug T.D. 3875' Set lost plug at 1300' with 20 and plug at 300' with 20 ard plug at 40' with 10 s Plug was down at 5:00 p.m. State Plugger - Gilbert Formula of Plugging Contractor STATE OF Kansas Jack L. Partridge, Aswell, being first duly swom on oath, says: | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from |
| was placed and the method or methology were used, state the character feet for each plug T.D. 3875' Set lost plug at 1300' with 20 and plug at 300' with 20 ard plug at 40' with 10 s Plug was down at 5:00 p.m. State Plugger - Gilbert Formula of Plugging Contractor STATE OF Kansas Jack L. Partridge, Aswell, being first duly swom on oath, says: | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from feet to set. th 70 sx. sx. 3. 3-20-77. Salthazor. scription is necessary, use BACK of this sheet) Abercrombie Drilling, Inc. court of Sedgwick ss. court of Genployee of owner) or (owner or operator) of the above described That I have knowledge of the facts, statements, and matters herein contained and the log of the same are true and correct. So help me Cod. (Signature) Add A Pathwace |
| was placed and the method or methology were used, state the character feet for each plug T.D. 3875' Set lost plug at 1300' with 20 and plug at 300' with 20 ard plug at 40' with 10 s Plug was down at 5:00 p.m. State Plugger - Gilbert Formula of Plugging Contractor STATE OF Kansas Jack L. Partridge, Aswell, being first duly swom on oath, says: | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from |
| was placed and the method or methology were used, state the character feet for each plug T.D. 3875' Set lost plug at 1300' with 20 and plug at 300' with 20 ard plug at 40' with 10 second plug at 40' with 10 second plug was down at 5:00 p.m. Plug was down at 5:00 p.m. State Plugger - Gilbert Feet plugger - Gilbert Fe | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from |
| was placed and the method or methology were used, state the character feet for each plug T.D. 3875' Set lost plug at 1300' with 20 and plug at 300' with 20 ard plug at 40' with 10 s Plug was down at 5:00 p.m. State Plugger - Gilbert Formula of Plugging Contractor STATE OF Kansas Jack L. Partridge, Aswell, being first duly swom on oath, says: | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from |
| was placed and the method or methology were used, state the character feet for each plug T.D. 3875' Set lost plug at 1300' with 20 and plug at 300' with 20 ard plug at 40' with 10 second plug at 40' with 10 second plug was down at 5:00 p.m. Plug was down at 5:00 p.m. State Plugger - Gilbert Feet plugger - Gilbert Fe | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from |
| was placed and the method or met plugs were used, state the chara feet for each plug T.D. 3875' Set lost plug at 1300' with 20 3rd plug at 300' with 20 3rd plug at 40' with 10 s Plug was down at 5:00 p.m. State Plugger - Gilbert E (If additional de Name of Plugging Contractor STATE OF Kansas Jack L. Partridge, As well, being first duly sworn on oath, says: above-described well as filed and that the | hods used in introducing it into the hold. If cement or othe cter of same and depth placed, from |
| was placed and the method or methology were used, state the character feet for each plug T.D. 3875' Set lost plug at 1300' with 20 and plug at 300' with 20 ard plug at 40' with 10 second plug at 40' with 10 second plug was down at 5:00 p.m. Plug was down at 5:00 p.m. State Plugger - Gilbert Feet plugger - Gilbert Fe | th 70 sx. sx. 3x. 1. 3-20-77. Salthazor. Scription is necessary, use BACK of this sheet) Abercrombie Drilling, Inc. Sedgwick St. SecTreas. (employee of owner) or (owner or operator) of the above-described That I have knowledge of the facts, statements, and matters herein contained and the log of the same are true and correct. So help-me God. (Signature) 801 Union Center, Wichita, Kansas 67202 |

