15-147-00027-00-00

STATE OF KANSAS STATE CORPORATION COMMISSION

WELL PLUGGING RECORD

Give All Information Completely Make Required Affidavit Mail or Deliver Report to: Conservation Division

FORMATION PLUGGING RECORD

Strike out upper line when reporting plugging off formations.

Conservation Division State Corporation Commission 800 Bitting Building						, <u>, , , , , , , , , , , , , , , , , , </u>
Wichita, Kansas		Phillips	Cou	inty. Sec. 23	Twp. 3	Rge(E) 18(W)
NORTH	Location as "NF	E¼NW¼SW¼"	or footage from	lines \mathcal{C}	ny ny	
						Well No. 1
						193
						193
						193
i						193
						199
	iteason for aban	dominent of wen			-	
	If a producing w	vell is abandoned				193
	Was permission					gging was commenced
Locate well correctly on abor Section Plat	TO					
ame of Conservation Agent who	supervised plugging of th	is well	T. Alexan	nder		
oducing formation	None De	pth to top	Botto	m	Total Depth	of Well 3736 Feet
ow depth and thickness of all w					-	
OIL, GAS OR WATER RE					CAS	SING RECORD
Formation	Content	From	То	Size	Put In	Pulled Out
		From				-
None				8-5/8"	2971	None
						-
						-
						-

		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				
	<u> </u>	A STATE OF THE STA		,		
	1/1	CI III		/		
		EIL : 2	3 3818	W	11104	9
	1011	2 5 4m²	40 1	171		
*	1171	800	and the second s			·
					* * * * * * * * * * * * * * * * * * *	
	1 10				: 11.11.11.11.11.11.11.11.11.11.11.11.11.	1.8
	' Pt :				AUG 25	10 / 😞
						TT /
				<i>b</i>	i d	/
	(If additional	description is necess	ry, use BACK of	this sheet)	*************************	10/0 25-6
Correspondence regarding thi	is well should be addressed	l to E.A.	Rose	*	 	5-00-7
ddress	Box 786, Great	Bend, Kan	ias		رواد د المراجع المراجع	and the same

			A SANCERA AND AND AND AND AND AND AND AND AND AN			
rate of Kans						
	E. A. Rose					
eing first duly sworn on oath, say			ements, and ma	tters herein cont	ained and the lo	g of the above-described
ell as filed and that the same ar	e true and correct. So he	elp me God.	/			
		(Signature)	As 1s	Koo.		
		(வதாகரமாக)	D ~	\\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	4.0	
		2	Dx 786	- Great	plud.	Kan
		·/e		(A	ddress)	
SUBSCRIBED AND SWORN TO b	before me this 2^{\vee}	lay of	ueses	1 194	2	
			10	2011	11	1.00
My Commis	ssion Expires July 29, 1	946	9	//// C	Jan	all
y commission expires				. // (;	//	Notary Public.
		173443	3–38—3M	i	<i> </i>	

CROW DRILLING COMPANY

422 COMMERCIAL NATIONAL BANK BUILDING

SHREVEPORT. LA.

Drillor's log on the Shew #1 well located in Section 83-5-18, Phillips County, Manage

```
170 * Shele
        197º Shale and shell
 170 * to
 197* to
        241 Shele and shell
        241 to
 200 to
         170 to 1770 to 16
 7701 63
        7001 424
 700 to 950 hand shale
 980* to
        COO! Tark send
 960 to 974 Nard sand
974 to 1000 Sand
1000' to 1075' Shale and shell
1078 to 1350 to 25 ale
1350' to 1364' Shale
1564' to 1262' Vime shale
1505' to 1650' Anhydrite a green shale
1030' to 1768' Shale and sholl
1705' to 1916' Shale
1016* to 2000* Shale
2000' to 2170' Shale and shell
2170' to 2230' Shale and 11me
2050' to 2361' Shale and shell
ssel* to 9425* Shele
2423' to 2464' Lime and shale
0464 to 2406 " Shale
PAGE TO BEST TARRE
PARTY to PROPERTY Line and shale
2580' to 2666' Mine and shale
2655' to 6735' Ame
2735 to 2745 24 to
2745' to 2772' Line and shale
2773' to SML4' Shale and Line
COLAT to COLET The let
2053 to 2012 thele and line
2012' to 2003' Shale and line
2053 to 3009 Shale and sand stroube
SOUTH TO TOTAL TO STREET
3027' to 3009' Lime
3039' to 3004' Lime and shale
3094 to 5099 14me
5000* to 5110* Kime soft
                               FILL = 23 3.918W
3110 to 7187 Line
5187* to 5189* Vine
                               BOOK JAGELLO NE-17
3133* to 3024* 1/20
```

5724* to 5252* 1/10

3013* to 5348* Mem 3345 to 3595 1/tme NAMES TO A SACRET AND ADDRESS TO THE SACL TO SACE THE Section to Section 2400' to 2010' Mass and shale SSIO' to SSEL' Shale & Line streeks 2551 to 2550 Orale and line 2500' to 5017' Shele and line 5617' to 5647' Charty shale Mar' to 2075' Mee and shale 3678' to 3707' Cherty lime 3707' to 3788' Gherty abale 3706' to 3756' Shale and lime Total Depth - 5786*

911,8-27-42 RIVE CONTRAINING