TO:	API number: 15-147_ 20241-00-00
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202	SW SE SW /4 SEC. 35 , 03 S, 19 W 330 feet from S section line feet from E section line
Operator license#_5252_	Lease Grau "B" well # 1
Operator: R.P. Nixon, Inc.	County Phillips 28
Operator: R.P. Nixon, Inc.  Address: 207 West 12th Street Hays, Kansas	Well total depth <u>3424</u> feet Conductor Pipe: <u>0</u> inch @ <u>0</u> feet Surface pipe 8 5/8 Inch @ <u>212</u> feet
Aband. oil well <u>X</u> , Gas well, Input well, SWD, D & A	
Plugging contractor: <u>Jay-Lan Corporation</u> License# <u>5128</u>	
Address: Hays, Kansas 67601	
Company to plug at: Hour: A.M. Day: 26 Month: October Year: 94	
Plugging proposal received from: Paul Nixon	
Company: R.P. Nixon, Inc.	Phone:
Were: Order 350 sxs. 60/40 pozmix - 10% gel - 500# hulls. Allied Cement Company.	
Plugging Proposal Received by: <u>Carl Goodrow</u> Plugging operations attended by agent? All[ X ], Part[ ], None[ ]	
Completed: Hour: P.M., Day: 26, Month: October, Year: 94	
Actual plugging report: 8 5/8" set @ 212' w/105 sxs. 4 1/2" set @ 3422' w/275 sxs. Prod. perfs. 3263' - 3383'. Squeezed 4 1/2" w/250 sxs.	
cement blend w/500# hulls mixed in to	Max. P.S.I. 1000#. Close in P.S.I.
200#. Work over rig on hole - squeezed holes at 2250' - 1800' - 1050' - 245' w/650 sxs. which circulated to surface. Squeezed 8 5/89TAWichro 25:00 COMMISSION	
sxs. cement blend. Blew casing. Plug	complete.
	11-8-94
Remarks:	CONSERVATION DIVISION
Condition of casing(in hole):GOODBAD_X Anhy.plug:YES_X NOBottom plug(in place):YES,CALC_X ,NOBakota plug:YES_X ,NOPlugged through TUBING, CASING_X . Elevation: GL	
	(tb)
DATE 11-9-94	(agent)
MY NO. 4/62/	

10-26