## 4-032005

10-3947-01001-00-01

TO:	API number: 15-147-20,246
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING	<u>NE NE SW</u> /4 SEC. 35 , 03 S, 19 W
200 COLORADO DERBY BUILDING	2310 feet from S section line
WICHITA, KANSAS 67202	_2970 feet from E section line
Operator license# 5252	Lease Grau "B" well # 4
Operator: R.P. Nixon, Inc.	County Phillips
Address: 207 West 12th Street	Well total depth <u>3616</u> feet
Hays, Kansas	Conductor Pipe: 0 inch @ 0 feet
	Surface pipe 8 5/8 Inch @ <u>1597</u> feet
Aband. oil well <u>X</u> , Gas well, Inp	ut well, SWD, D & A
Plugging contractor: <u>Jay-Lan Corporation</u> License# <u>5128</u>	
Address: <u>Hays, Kansas 67601</u>	
Company to plug at: Hour: A.M. Day:	26 Month: October Year: 94
Plugging proposal received from: Paul	Nixon
Company: R.P. Nixon, Inc. Phone:	
Were: Order 350 sxs. 60/40 pozmix - 10% gel - 500# hulls. Allied Cement Company.	
Allied Cement Company.	
Plugging Proposal Received by: <u>Carl Goodrow</u> Plugging operations attended by agent? All[X], Part[], None[]	
Completed: Hour: 12:40P.M, Day: 26, Mo	nth: October , Year: 94
Actual plugging report: 8 5/8" set @ 1597' cwc. 4 1/2" set @ 3597'	
W/125 sxs. P.B.T.D. 3323'. Prod. perfs. 3315' - 3414'. Critical area	
control shots at 925' and 1500'. Squeezed 4 1/2" w/175 sxs. cement blend w/500# hulls mixed in to Max. P.S.I. 500#. Close in P.S.I. 100#.	
Squeezed 8 5/8" with 40 sxs. cement blend to Max. P.S.I. 500#. Close	
in P.S.I. 0#. Blew out head. Plug con	mplete.
	STATE CORPORATION
	STATE CORPORATION COMMI
Remarks:	AD Anhy.plug:YES X NO NO 8 1994
Condition of casing(in hole):GOOD ★ Bi Bottom plug(in place):YES,CALC ★ Plugged through TUBING . CASING ★	ADAnhy.plug:YES_X_NO
Plugged through TUBING, CASINGX	Elevation: GL WICHE DIVISION
I did X ] O did no [ ] observe the pi	A D O
DATE 11-9-94	(agent)
41624	Form CP-2/3

10-26