

STATE OF KANSAS  
STATE CORPORATION COMMISSION

FORM CP-1

Rev. 03/92

RECEIVED  
AUG 11 2004  
KCC WICHITA

CONSERVATION DIVISION

130 S. Market, Room 2078  
Wichita, Kansas 67202

WELL PLUGGING APPLICATION FORM  
(PLEASE TYPE FORM and File ONE Copy)

API #: 15-185-23266-0000 (Identifier number of this well). This must be listed for wells drilled since 1967; if no API# was issued, indicate spu or completion date

WELL OPERATOR: Mull Drilling Co., Inc.  
(owner/company name)

KCC LICENSE # 5144  
(operator's)

ADDRESS: P.O. Box 2758 CITY: Wichita

STATE: Kansas ZIP CODE: 67201-2758 CONTACT PHONE: 316-264-6366

LEASE: Baier WELL#: 1-7 Section 7 Township 22s Range 13w

Approximately S/2 S/2 Nw of SPOT LOCATION/QQQQ COUNTY: Stafford

1300 FEET (in exact footage) FROM West LINE OF SECTION (NOT Lease Line)

2310 FEET (in exact footage) FROM North LINE OF SECTION (NOT Lease Line)

Check One: Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ D&A XX SWD/ENHR WELL \_\_\_\_\_ Docket # \_\_\_\_\_  
CONDUCTOR CASING SIZE None SET AT NA CEMENTED WITH NA SACKS  
SURFACE CASING SIZE 8-5/8" SET AT 296' KB CEMENTED WITH 275 SACKS  
PRODUCTION CASING SIZE None SET AT \_\_\_\_\_ CEMENTED WITH \_\_\_\_\_ SACKS

LIST (ALL) PERFORATIONS and BRIDGEPLUG SETS:  
ELEVATION 1913 G.L. 1922 K.B. T.D. 3870 PBSD \_\_\_\_\_ Anhydrite Depth 805  
(Stone Corral Formation)  
CONDITION OF WELL: GOOD XX POOR \_\_\_\_\_ CASING LEAK \_\_\_\_\_ JUNK IN HOLE \_\_\_\_\_

PROPOSED METHOD OF PLUGGING:  
Received plugging orders on 08/08/04. Heavy mud in hole and between all plugs. Bottom plug at 3840'/40 sx,  
2nd plug at 850'/50sx, 3rd plug at 350'/50sx and top plug at 40'/15sx cemented to surface. Total of 160sx 60/40 Poz;  
6% Gel in hole. Plugged rathole using 15sx same blend, no mousehole. Plugging completed 2:30 am on 08/09/04.  
Acid Services ticket #8159. SDC reported plugging to KCC on 08/09/04.  
IS WELL LOG ATTACHED TO THIS APPLICATION AS REQUIRED? Yes (YES,NO) IS ACO-1 FILED? ? (YES,NO)  
If not explain why? \_\_\_\_\_

PLUGGING OF THIS WELL WILL BE DONE IN ACCORDANCE WITH K.S.A. 55-101 et. seq. AND THE RULES AND REGULATIONS OF THE STATE CORPORATION COMMISSION.

LIST NAME OF COMPANY REPRESENTATIVE AUTHORIZED TO BE IN CHARGE OF PLUGGING OPERATIONS:  
Name: Gary Pugh/Gary Talbott Phone#: (316) 672-9508  
Address: P.O. Box 1006 City: Pratt State: Kansas  
PLUGGING CONTRACTOR: Sterling Drilling Company KCC LICENSE #: 5142  
(company name) (contractor's)  
Address: P.O. Box 1006 City: Pratt State: Kansas Zip 67124

PROPOSED DATE AND HOUR OF PLUGGING (If Known?) Plugged well at 2:30 am on August 09, 2004. Plugged  
PAYMENT OF THE PLUGGING FEE (K.A.R. 82-3-118) WILL BE GUARANTEED BY: Operator X Agent \_\_\_\_\_

DATE: 08/09/04 AUTHORIZED OPERATOR OR AGENT: Gary M. Talbott  
(signature) Gary M. Talbott, Agent for Operator

# Sterling Drilling Company, Rig #1

Box 1006, Pratt, Kansas 67124-1006  
Office Phone (620) 672-9508, Fax 672-9509

## SAMPLE LOG

## Baier 1-7

**LOCATION:** Approximately S/2 S/2 Nw of Section 7 T 22s R 13w  
**API:** 15-185-23266-0000 Stafford County, Kansas

**OWNER:** Mull Drilling Co., Inc.  
**CONTRACTOR:** Sterling Drilling Company, Rig #1

**COMMENCED:** 02-Aug-04  
**COMPLETED:** 09-Aug-04

**TOTAL DEPTH:** **DRILLER** 3870 FEET  
**LOGGER** Did not log FEET

**Ground Elevation:** 1913  
**KB Elevation:** 1922

### LOG

0 -	1 FEET	Top Sand
1 -	8 FEET	Clay
8 -	21 FEET	Sand and Gravel
21 -	90 FEET	Sand and Gravel
90 -	185 FEET	Sand and Clay
185 -	805 FEET	Redbeds
805 -	835 FEET	Anhydrite (Driller's)
835 -	1620 FEET	Shales and Salt
1620 -	3840 FEET	Limestone, Shale and Dolomite
3840 -	3870 FEET	Arbuckle

### CASING RECORDS

#### Surface Casing-8-5/8"

Spud at 3:15 pm on 08/02/04. Drilled 12-1/4" hole to 296'. Ran 9 joints of used 28# 8-5/8" surface casing, tally 300' set at 296' KB. Cemented with 275 sx Class A, 3% CC, 2% Gel, Cement did circulate. Plug down at 8:30 pm on 08/02/04. Allied Cementing ticket #17315. Welded straps on bottom 3 joints, tacked collars on remaining 6 joints.

#### Production Casing

Received plugging orders on 08/08/04. Heavy mud in hole and between all plugs. Bottom plug at 3840'/40 sx, 2nd plug at 850'/50sx, 3rd plug at 350'/50sx and top plug at 40'/15sx cemented to surface. Total of 160sx 60/40 Poz; 6% Gel in hole. Plugged rathole using 15sx same blend, no mousehole. Plugging completed 2:30 am on 08/09/04. Acid Services ticket #8159. SDC reported plugging to KCC on 08/09/04.

### DEVIATION SURVEYS

3/4	degree(s) at	240	feet
1	degree(s) at	3850	feet