

4-060782

V 10-9

API Number: 15-137-20,396 0000

TO: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
130 SOUTH MARKET, SUITE 2078  
WICHITA, KANSAS 67202

SW NW NE /4 SEC. 09, 03 S, 24 W  
4290 feet from S section line  
2310 feet from E section line

Operator license# 5050

Lease: Maddy Ranch Well # 1

Operator: Hummon Corporation

County: Norton

Address: 200 W. Douglas - #1020  
Wichita, Kansas 67202

Well total depth 3686 <sup>119.80</sup> feet  
Conductor Pipe: 0 inch @ 0 feet  
Surface pipe 8 5/8 Inch @ 231 feet

Aband. oil well\_\_\_, Gas well\_\_\_, Input well\_\_\_, SWD\_\_\_, D & A X

Plugging contractor: Nebraska Drilling Company License# 31730

Address: P.O. Box 370 - Gainesville, Texas 76241

Company to plug at: Hour: A.M. Day: 9 Month: October Year: 1995

Plugging proposal received from: \_\_\_\_\_

Company: Nebraska Drilling Company Phone: \_\_\_\_\_

Were: Order 200 sxs 60/40 posmix - 6% gel with 1/4# floseal per sack.  
Space all plugs with heavy drilling mud through drill pipe.

Plugging Proposal Received by: Herb Deines

Plugging operations attended by agent? All[ ], Part[ ], None[ X ]

Completed: Hour: A.M., Day: 9, Month: October, Year: 1995

Actual plugging report: \_\_\_\_\_

1st. Plug at 1960' w/25 sxs. - Anhydrite 1949' - 1979'.

2nd. Plug at 1300' w/100 sxs. - Dakota 1000' - 1300'.

3rd. Plug at 300' w/40 sxs. - Surface pipe to 331'.

4th. Plug at 40' w/10 sxs.

Mousehole with 10 sxs.

Rathole with 15 sxs.

RECEIVED  
KANSAS CORPORATION COMMISSION  
DEC 08 1995  
12-8-95  
CONSERVATION DIVISION  
WICHITA, KS

Remarks: Allied Cementing.

Condition of casing(in hole): GOOD\_\_\_ BAD\_\_\_ Anhy.plug: YES X NO\_\_\_

Bottom plug(in place): YES\_\_\_, CALC\_\_\_, NO X Dakota plug: YES X, NO\_\_\_

Plugged through TUBING\_\_\_, CASING\_\_\_ Elevation: 2400 GL

I did [ ] / did not [ X ] observe the plugging.

Herb Deines  
(agent)  
Form CP-2/3

INVOICED  
DATE 12-8-95  
INV. NO. 44284