STATE OF KANSAS

STATE CORPORATION COMMISSION

Give All Information Completely

Make Required Affidavit

Mail or Deliver Report to:

Conservation Division

State Corporation Commission

800 Bitting Building

15-039-00666-00-00

WELL PLUGGING RECORD

800 Bitting Building Wichita, Kansas	Decat					
NORTH	Location as "NI Lease Owner	E/CNW#SW#" Ashlan d	or footage fro	m lines Compa	SE SW NW any	
	Lease Owner Lease Name	Myron Pol	lnow			_ Well No. 1
	Office Address_			ahoma City		
	Character of W Date well comp	ell (completed loted lot	l as Oil, Gas o -53	r Dry Hole)	Dry note	19
	Application for		10-4			19
	Application for		oved 10-4- 10-4-53	-3 3		19
	Plugging comm Plugging compl	70		The second secon		19
	Reason for abar		ell or producin	g formation	Dry Hole	10
				st production		ore plugging was com
Locate well correctly on above Section Plat	$\frac{\mathbf{Y}}{\mathbf{Y}}$	es				
me of Conservation Agent who		5 W C11		ty, H ays , 1		Well 3950 For
oducing formation Hone ow depth and thickness of all w			Botton	1	Total Depth of	Well 3930 Fee
OIL, GAS OR WATER RECO	, -					CASING RECORD
	CONTENT	FROM	то	SIZE	PUT IN	PULLED OUT
FORMATION Shawnee	Salt water	3650	3660	8-5/8"	191.5	None
		The The The State of the State		***************************************		, , , , , , , , , , , , , , , , , , , ,
feet for each plus 1 plus 2 plus 1 plus 1	cement or other plugs we ag set. idge plug @ 185† 5 sxs cement. T 40† to 41†. Fil 0 sxs. cement.	to 186† v hen filled	with 1/2 and with head of to sur	f same and dept sack of co avy drilling rface with	tton seed l	hulls on top 40'. Set bridg
introducing it into the hole. If feet for each plu Set br plus 1 plug @ plus 1	cement or other plugs we ag set. idge plug @ 185† 5 sxs cement. T 40† to 41†. Fil	to 186† v hen filled	with 1/2 and with head of to sur	f same and dept sack of co avy drilling rface with	tton seed l	hulls on top
introducing it into the hole. If feet for each plu Set br plus 1 plug @ plus 1	cement or other plugs we ag set. idge plug @ 185† 5 sxs cement. T 40† to 41†. Fil 0 sxs. cement.	to 186† v hen filled	with 1/2 and with head of to sur	f same and dept sack of co avy drilling rface with	tton seed l	hulls on top 40'. Set bridg
introducing it into the hole. If feet for each plu Set br plus 1 plug @ plus 1	cement or other plugs we ag set. idge plug @ 185† 5 sxs cement. T 40† to 41†. Fil 0 sxs. cement.	to 186† v hen filled	with 1/2 and with head of to sur	f same and dept sack of co avy drilling rface with	tton seed l	hulls on top
introducing it into the hole. If feet for each plu Set br plus 1 plug @ plus 1	cement or other plugs we ag set. idge plug @ 185† 5 sxs cement. The 40 to 41 fill of sxs. cement. Ing was performed	to 186† v hen filled	with 1/2 and with head of to sur	f same and dept sack of co avy drilling rface with	tton seed l	hulls on top
feet for each plus 1 plus 2 plus 1 plus 1 plus 1 plus 1	cement or other plugs we ag set. idge plug @ 185† 5 sxs cement. The 40 to 41 fill of sxs. cement. Ing was performed	to 186† v hen filled led from	with 1/2 state of the state of	sack of convergence of the sack of t	tton seed ling mud to	hulls on top
feet for each plus 1 plus 2 plus 1 plus 1 plus 1 plus 1	cement or other plugs we ag set. idge plug @ 185† 5 sxs cement. The 40 to 41 fill of sxs. cement. Ing was performed	to 186† v hen filled led from	with 1/2 and with head of to sur	sack of coavy drilling ace with	tton seed ling mud to	hulls on top 40'. Set bridg
feet for each plus 1 plus 2 plus 1 plus 1 plus 1 plus 1	cement or other plugs we ag set. idge plug @ 185† 5 sxs cement. The 40 to 41 fill of sxs. cement. Ing was performed	to 186† v hen filled led from	with 1/2 state of the state of	sack of convergence of the sack of t	tton seed ling mud to	hulls on top 40'. Set bridg
introducing it into the hole. If feet for each plu Set br plus 1 plug @ plus 1 Pluggi	cement or other plugs we ag set. idge plug @ 185† 5 sxs cement. The 40 to 41 fill of sxs. cement. Ing was performed	to 186† v hen filled led from through o	with 1/2 state of the character of the c	f same and dept sack of co avy drilling rface with co OGT 1	tton seed ling mud to	hulls on top 40'. Set bridg
me of Plugging Contractor	cement or other plugs we ag set. idge plug @ 185† 5 sxs cement. The 40' to 41'. Fill to 30 sxs. cement. Ing was performed the base of t	to 186† when filled led from through of thro	with 1/2 state of the character of the third with he state of the surface of the surface of the third with he state of the third with the surface of the sur	f same and dept sack of co avy drilling rface with continuous OCT 1	tton seed ling mud to 1/2 sack of the control of th	hulls on top 40'. Set bridg cotton seed hu
me of Plugging Contractor_dress	cement or other plugs we ag set. idge plug @ 185* 5 sxs cement. To 40* to 41*. Fill 0 sxs. cement. Ing was performed Hannum Drilling on National Build ma [owrey] th, says: That I have knot that the same are true and the same are true an	to 186† when filled led from through of through of the company ing, Wich:	with 1/2 and with head of the surface of the surfac	sack of convergence of this sheet) as a www.er) or (***********************************	tton seed ling mud to 1/2 sack of the control of th	hulls on top 40°. Set bridg cotton seed hu
introducing it into the hole. If feet for each plu Set br plus 1 plug @ plus 1 Pluggi Pluggi Matter Of Contractor Unio	cement or other plugs we ag set. idge plug @ 185* 5 sxs cement. To 40* to 41*. Fill 0 sxs. cement. Ing was performed Hannum Drilling on National Build ma [owrey] th, says: That I have knot that the same are true and the same are true an	to 186† when filled led from through of through of the company ing, Wich: NTY OF	with 1/2 and with head of the surface of the surfac	of this sheet) as owner) or (**** The way drilling of the sheet) as owner) or (**** The way drilling of the sheet) as owner) or (**** The way drilling of the sheet)	tton seed ling mud to 1/2 sack of the control of th	hulls on top 40°. Set bridg cotton seed hu
me of Plugging Contractor dress Oklaho Bill M ll, being first duly sworn on oar ove-described well as filed and	idge plug @ 185* 5 sxs cement. To 40 to 41. Fill O sxs. cement. Ing was performed Hannum Drilling on National Build ma (owrey) th, says: That I have knothat the same are true and the same are	description is need company ing, Wich: NTY OF	with 1/2 at with head of to sure state. STATE Oklahoma employee of cacts, statement help me God. State P.O. Box	of this sheet) as a owner) or (State) as a owner) or (State) as a owner) or (State)	tton seed ling mud to 1/2 sack (1/2	hulls on top 40°. Set bridg cotton seed hu
me of Plugging Contractor_dress	idge plug @ 185* 5 sxs cement. To 40 to 41. Fill O sxs. cement. Ing was performed Hannum Drilling on National Build ma (owrey) th, says: That I have knothat the same are true and the same are	description is need company ing, Wich: NTY OF	with 1/2 at with head of to sure state. STATE Oklahoma employee of cacts, statement help me God. State P.O. Box	of this sheet) as a bwner) or (Asia) Thousand matter	tton seed lang mud to 1/2 sack of 1/2 sack	hulls on top 40°. Set bridg cotton seed hu
me of Plugging Contractor_dress Unio ATE OF Oklaho Bill M Subscribed and Sworn to be seek for each plus 1 plug @ plus 1 pluggi	idge plug @ 185* 5 sxs cement. To 40 to 41. Fill O sxs. cement. Ing was performed Hannum Drilling on National Build ma (owrey) th, says: That I have knothat the same are true and the same are	description is need company ing, Wich: NTY OF	with 1/2 at with head of to sure state. STATE Oklahoma employee of cacts, statement help me God. State P.O. Box	of this sheet) as a owner) or (State) as a owner) or (State) as a owner) or (State)	tton seed lang mud to 1/2 sack of 1/2 sack	hulls on top 40°. Set bridg cotton seed hu

PLUGGING
PLU