

Company Harry Gore

Farm Burns

No. 1

Sec. 16 T. 3 R. 28


Loc. NE NE NE

County Decatur - Kansas

15-039-00042-00-00

Total Depth 4390'
Comm. 8-7-51

Comp. 8-20-51



Shot or Treated

Contractor Veeder Supply Company

Drilled with Rig - D

Issued

No. of Days - 14

No. of Bits -

Casing

20 in. 10 in
15 1/2 8 1/4
12 1/2 6 5/8
13 3/8 5 3/16

Set 206' of 8-5/8" Csg. Cemented with 125 sacks cement.

Elevation

Production

Figures Indicate Bottom of Formation

Surface Soil	0	70	70
Lime Sand	70	180	110
Lime Shale	180	275	95
Shale	275	890	615
Shells Shale	890	1400	510
Sand Shale	1400	1550	150
Shale Shells	1550	1860	310
Shale Shells Sand	1860	1940	80
Shale Shells	1940	2040	100
Lime Shells Shale	2040	2240	200
Shale Shells Red Bed	2240	2423	183
Anhydrite	2423	2458	35
Shale Shells	2458	2600	142
Sandy Shale	2600	2840	240
Shale Lime Shells	2840	2958	118
Lime Shale	2958	3750	792
Lime	3750	4025	275
Lime Shale	4025	4210	185
Conglomerate	4210	4320	110
Lime	4320	4390	70
Total Depth	4390'		

Plugged @ 195' with 15 sacks cement.
Plug ed @ 40' with 10 sacks cement.

RECORDED
STAMP

SEP 13 1951

PLUGGING
FILE SEC 16 T 3 R 28W
BOOK PAGE 104 LINE 28