

6 040914

5-16

API NUMBER 15- 147-20,145-00-00

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

NW SW NE, SEC. 30, T 4 S, R 19 W/E  
\_\_\_\_\_ feet from S section line  
\_\_\_\_\_ feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5242

Operator: Petroleum Mgmt Inc.  
Name & Address: 400 N. Woodlawn  
Suite 201  
Wichita, Ks. 67208

Lease Name Adee Well # 3  
County Phillips 110.83  
Well Total Depth 3410 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 202' w/145

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Allied Cementing License Number \_\_\_\_\_

Address Russell, Ks.

Company to plug at: Hour: 10:15AM Day: 16 Month: May Year: 19 88

Plugging proposal received from Wayne Fuzzell

(company name) Pet. M.I. (phone) \_\_\_\_\_

were: Ordered 250 sks 65/35 Poz 10% Gel 2% Lite w/1/4# F.C. plus 6 sks Hulls.

RECEIVED  
STATE CORPORATION COMMISSION

OCT 21 1988  
10-21-88  
CONSERVATION DIVISION  
Wichita, Kansas

Plugging Proposal Received by \_\_\_\_\_ (TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 10:15AM Day: 16 Month: May Year: 19 88

ACTUAL PLUGGING REPORT 5 1/2" set at 3409' w/225 sks. Top perf at 3157'.

Plugged bottom 3100' w/sand and 5 sks cement to 3100'. Shot pipe at 1500' and 658' and recovered 658'. Pumped in 8 5/8" 250 sks A.T.L. w/1/4# F.C. plus 6 sks Hulls in cement.

Remarks: \_\_\_\_\_  
(If additional description is necessary, use BACK of this form.)

INVOICED  
(If applicable, observe this plugging.)

DATE 10-25-88

INV. NO. 22716

Signed Dennis L. Hamel  
(TECHNICIAN)  
Dennis L. Hamel