

STATE OF KANSAS
STATE CORPORATION COMMISSION
CONSERVATION DIVISION

FORM CP-1

Rev. 03/92

RECEIVED
JAN 12 2004
KCC WICHITA

130 S. Market, Room 2078
Wichita, Kansas 67202

WELL PLUGGING APPLICATION FORM
(PLEASE TYPE FORM and File ONE Copy)

API #: 15-077-21468-0000 (Identifier number of this well). This must be listed for wells drilled since 1967; if no API# was issued, indicate spu or completion date

WELL OPERATOR: Becker Oil Corporation KCC LICENSE # 31093
(owner/company name) (operator's)

ADDRESS: 122 E. Grand St., Ste. 212 CITY: Ponca City
STATE: Oklahoma ZIP CODE: 746601 CONTACT PHONE: 303-816-2013
LEASE: Mathes WELL#: 1-A Section 29 Township 31s Range 7w
Ne Nw Ne SPOT LOCATION/QQQQ COUNTY: Harper

265 FEET (in exact footage) FROM North LINE OF SECTION (NOT Lease Line)
1315 FEET (in exact footage) FROM East LINE OF SECTION (NOT Lease Line)

Check One: Oil Well _____ Gas Well _____ D&A XX SWD/ENHR WELL _____ Docket # _____
CONDUCTOR CASING SIZE None SET AT NA CEMENTED WITH NA SACKS
SURFACE CASING SIZE 8-5/8" SET AT 239' KB CEMENTED WITH 200 SACKS
PRODUCTION CASING SIZE None SET AT _____ CEMENTED WITH _____ SACKS

LIST (ALL) PERFORATIONS and BRIDGEPLUG SETS:
ELEVATION 1501 G.L. 1510 K.B. T.D. 2240 PBD _____ Anhydrite Depth ? _____
(Stone Corral Formation)
CONDITION OF WELL: GOOD XX POOR _____ CASING LEAK _____ JUNK IN HOLE _____

PROPOSED METHOD OF PLUGGING:
Received plugging orders from Doug Lewis on 12/29/03. Plugged using 160 sx 60/40 Poz; 4% Gel.
Heavy mud in hole and between all plugs. Bottom plug @ 1500'/35sx; 2nd plug @ 1000'/35sx;
3rd plug @ 290'/50sx; top plug @ 60'/25 sx cemented to surface. Plugged rathole 15 sx, no mousehole.
Plugging completed at 7:00 am 12/30/03 by Allied Cementing, ticket # 15028. Reported to KCC 12/30/03.
IS WELL LOG ATTACHED TO THIS APPLICATION AS REQUIRED? Yes (YES,NO) IS ACO-1 FILED? ? (YES,NO)
If not explain why? _____

PLUGGING OF THIS WELL WILL BE DONE IN ACCORDANCE WITH K.S.A. 55-101 et. seq. AND THE RULES AND REGULATIONS OF THE STATE CORPORATION COMMISSION.

LIST NAME OF COMPANY REPRESENTATIVE AUTHORIZED TO BE IN CHARGE OF PLUGGING OPERATIONS:
Name: Lanny Saloga /Gary Talbott Phone#: (316) 672-9508
Address: P.O. Box 1006 City: Pratt State: Kansas
PLUGGING CONTRACTOR: Sterling Drilling Company KCC LICENSE #: 5142
(company name) (contractor's)
Address: P.O. Box 1006 City: Pratt State: Kansas Zip 67124

PROPOSED DATE AND HOUR OF PLUGGING (If Known?) Plugged well at 7:00 am on December 30, 2003. **Plugged**
PAYMENT OF THE PLUGGING FEE (K.A.R. 82-3-118) WILL BE GUARANTEED BY: Operator X Agent _____

DATE: 12/30/03 AUTHORIZED OPERATOR OR AGENT: Gary M. Talbott
(signature) Gary M. Talbott, Agent for Operator

Sterling Drilling Company, Rig #4

Box 1006, Pratt, Kansas 67124-1006
Office Phone (620) 672-9508, Fax 672-9509

SAMPLE LOG

Mathes 1-A

LOCATION: Ne Nw Ne
API: 15-077-21468-0000

Section 29 T 31s R 7w
Harper County, Kansas

OWNER: Becker Oil Corporation
CONTRACTOR: Sterling Drilling Company, Rig #4

COMMENCED: 22-Dec-03
COMPLETED: 30-Dec-03

TOTAL DEPTH: **DRILLER** 2240 FEET
LOGGER No Log FEET

Ground Elevation: 1501
KB Elevation: 1510

LOG

0 -	2 FEET	Top Soil
2 -	205 FEET	Clay
205 -	880 FEET	Redbeds
880 -	1380 FEET	Shales and Salt
1380 -	2240 FEET	Limestone, Shale and Dolomite

CASING RECORDS

Surface Casing-8-5/8"

Spud at 10:00 am on 12/22/03. Drilled 12-1/4" hole to 245'. Ran 5 joints new, 23# 8-5/8" surface casing. Tally 228' set at 239' KB. Cemented with 200 sx 60/40 Poz; 3% CC. 2% Gel, 1% Ammonia. Cement did circulate. Plug down at 4:45 pm on 12/22/03. By Allied Cementing. Ticket # 14603. Strapped bottom 3 joints, welded collars on remaining 2 joints of surface casing.

ProDUCTION Casing

Received plugging orders from Doug Lewis on 12/29/03. Plugged using 160 sx 60/40 Poz; 4% Gel. Heavy mud in hole and between all plugs. Bottom plug @ 1500'/35sx; 2nd plug @ 1000'/35sx; 3rd plug @ 290'/50sx; top plug @ 60'/25 sx cemented to surface. Plugged rathole 15 sx, no mousehole. Plugging completed at 7:00 am 12/30/03 by Allied Cementing, ticket # 15028. Reported to KCC 12/30/03.

DEVIATION SURVEYS

3/4	degree(s) at	245	feet
1/2	degree(s) at	780	feet
0	degree(s) at	1540	feet
1	degree(s) at	2240	feet