

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-039-30070-00-01
Spot: NESENW , Sec/Twnshp/Rge: 9-4S-27W
3630 feet from S Section Line, 2970 feet from E Section Line
Lease/Unit Name: PETRACEK Well Number: 1
County: DECATUR Total Vertical Depth: 4040 feet

Operator License No.: 5363

Production Casing Size: 5.5 feet: 4040 200 SX CMT 131.30
Surface Casing Size: 8.625 feet: 202 175 SX CMT

Op Name: BEREXCO, INC.

Address: PO BOX 20380
WICHITA, KS 67208

Well Type: EOR

UIC Docket No: E27325.1

Date/Time to Plug: 02/27/2003 10:00 AM

Plug Co. License No.: 5363

Plug Co. Name: BEREXCO, INC.

Proposal Rcvd. from: CURT GABEL

Company: BEREXCO, INC.

Phone: (785) 628-6101

Proposed Plugging Method: Order 350 sxs 60/40 pozmix - 10% gel - 600# hulls.
Plug through 2 7/8" tubing.
Pump 50 sxs between 8 5/8" surface casing and 5 1/2" production casing.

Plugging Proposal Received By: HERB DEINES

Witness Type: Plugging Operations 100% Witnessed (Complete)

Date/Time Plugging Completed: 02/27/2003 12:40 PM

KCC Agent: DARREL DIPMAN

Actual Plugging Report:

Perforations 3284' - 3648'. PBTD 4035'.
8 5/8" S.P. set at 202' cwc with 175 sxs.
5 1/2" set at 4040' w/200 sxs.
Ran 2 7/8" tubing to 3275' - pumped 100 sxs cement with 300# hulls.
Pulled 2 7/8" tubing to 1880' - pumped 100 sxs cement with 100# hulls. Cement to surface.
Pulled 2 7/8" tubing to surface. Connected to 5 1/2" casing and pumped 90 sxs cement.
Max. P.S.I. 500#. S.I.P. 200#.
Connected to 8 5/8" surface casing. Pumped 15 sxs cement.
Max. P.S.I. 300#. S.I.P. 200#.

Remarks: ALLIED CEMENTING COMPANY.

Plugged through: TBG

District: 04

Signed

Darrel Dipman

(TECHNICIAN)

HO
RECEIVED

MAR 13 2003

KCC WICHITA

INVOICED

Form CP-2/3


DATE 3-14-03

INV. NO. 200.3061297

MAR 11 2003

WILDCAT

11-173 Map No. _____
 OPER OKMAR OIL CO.
 WICHITA, KS.
 WELL #1 PETRACEK
 CONTR LEBEN DRLG.
 WC DISC. OF PETRACEK FIELD (LAN OIL)
 I.P. STATE POT: P 117 BOPD + 1% WTR GR 35 DEG
 LAN 3643-48



S-T-R 9-4S-27W
 SPOT NE SE NW
 CO DEGATUR
 ELEV 2669 KB

KB SPL TOPS:	
ANH	2178 + 491
B/ANH	2212 + 457
TOP	3400 - 731
HB	3518 - 849
TOR	3548 - 879
LAN	3562 - 893
BKC	3761 -1092
CGL	3932 -1263
GW	4015 -1346
RTD	4040 -1371

SPD 9-9-66 8" @202/175 SX MAX HOUSTON, GEOL
 (DISC PETRACEK FIELD (LAN OIL))

DST #1 (TOP) 3404-69, OP 2 HRS, R 180'M + 90'W, ISIP 830#/30", FP 0-80#, FSIP 830#/30"

DST #2 (LAN) 3553-80, OP 2 HRS, R 30'OIL + 50'HOCM, ISIP 610#/30", FP 20-50#, FSIP 280#/30"

DST #3 (LAN) 3575-3620, OP 1 HR, 2220'GIP, R 870'OIL (GR (GR EST 38-40 DEG), ISIP 1100#/30", FP 50-300#, FSIP 1040/30"

DST #4 (LAN) 3618-65, OP 60", 180'GIP, R 62'HOGCM, ISIP 870#/30"FP 0-40#, FSIP 560#/30"

DST #5 (LAN) 3661-95, OP 60", R 15'SOCM, ISIP 100#/30", FP 0-0, FSIP 0#/30"

DST #6 (LAN) 3683-3765, OP 1 HR, R 6'M, ISIP 0#/30", FP 0-0 FSIP 0#/30"

RTD 4040' - NO LOG - 5 1/2" @4040/200 SX (35'HIGH)

Datta Inc