

4-061173

TO: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
130 SOUTH MARKET, SUITE 2078  
WICHITA, KANSAS 67202

12-15

API Number: 15-137-20,410 00-00

NW SE NW /4 SEC. 24, 04 S, 22 W  
3630 feet from S section line  
3630 feet from E section line

Operator license# 30425

Lease: Greving Well # 22-24

Operator: DNR Oil & Gas, Inc.

County: Norton 122,20

Address: 655 Broadway - Suite #525  
Denver, CO 80203

Well total depth 3760 feet  
Conductor Pipe: 0 inch @ 0 feet  
Surface pipe 8 5/8 Inch @ 262 feet

Aband. oil well\_\_\_, Gas well\_\_\_, Input well\_\_\_, SWD\_\_\_, D & A X

Plugging contractor: Murfin Drilling Company License# 30606

Address: Wichita, Kansas 67202

Company to plug at: Hour: 3:00 A.M. Day: 15 Month: December Year: 1998

Plugging proposal received from: Keith VanPelt

Company: Murfin Drilling Company Phone: -

Were: Order 190 sxs 60/40 posmix - 6% gel with 1/4# flocele per sack.  
Space all plugs with heavy drilling mud through drill pipe.

Plugging Proposal Received by: Herb Deines

Plugging operations attended by agent? All[ ], Part[ ], None[ X ]

Completed: Hour 5:45 A.M., Day: 15, Month: December, Year: 1998

Actual plugging report:

1st. Plug at 1860' w/25 sxs. Anhydrite 1833' - 1863'.

2nd. Plug at 1065' w/100 sxs. Dakota 758' - 1058'.

3rd. Plug at 315' w/40 sxs. Surface pipe - 262'.

4th. Plug at 40' w/10 sxs.

Rathole with 15 sxs.

Remarks: Allied Cementing.

Condition of casing(in hole): GOOD X BAD \_\_\_\_\_ Anhy.plug: YES \_\_\_\_\_ X NO \_\_\_\_\_

Bottom plug(in place): YES \_\_\_\_\_, CALC \_\_\_\_\_, NO X Dakota plug: YES X, NO \_\_\_\_\_

Plugged through TUBING \_\_\_\_\_, CASING \_\_\_\_\_. Elevation: 2183 GL

I did[ ] / did not[ X ] observe the plugging.

[Signature]  
(agent)

DH

Form CP-2/3

12-22-98

DEC 29 1998

60485