10-14 4-041623 15-147-00872-00-00

TO:	API number: 15 5-4-1942
STATE CORPORATION COMMISSION	
CONSERVATION DIVISION - PLUGGING 200 COLORADO DERBY BUILDING	<u>SW SW SW</u> /4 SEC. <u>29 , 05 S, 20 W</u> <u>330 feet from S section line</u>
WICHITA, KANSAS 67202	4950 feet from E section line
Operator license#_5447	Lease_Pinkerton "A" well #_6
Operator: OXY USA, Inc.	County Phillips
Address: 110 S. Main	Well total depth 3604 feet Conductor Pipe: 0 inch 0 0 feet
Suite #800	Conductor Pipe: 0 inch @ 0 feet
Wichita, Kansas 67202	Surface pipe 8 5/8 Inch @ 153 feet
Aband. oil well <u>x</u> , Gas well <u></u> , Inp	w/125 sxs. out well, SWD, D & A
Plugging contractor: <u>Halliburton Cementing</u> License#	
Address: <u>Hays, Kansas</u> 67601	
Company to plug at: Hour: 9:00A.M. Day: 14 Month: October Year: 94	
Plugging proposal received from: Jim Nowell	
Company: OXY USA, Inc. Phone:	
Were: 5 1/2" casing set @ 3559' w/100 sxs. cement. O.H. @ 3595' - 3604'. Anhy. @ 1785' - Dakota @ 1075' - W.L.M. @ 3600' - T.O.F. @ 1800'. Ordered 325 sxs. 60/40 pozmix - 10% gel with 1/4# F.C. plus 500# hulls.	
Plugging Proposal Received by: Dennis L. Hamel	
Plugging operations attended by agent? All[], Part[X], None[]	
Completed: Hour: 10:00P.M, Day: 14, Month: October, Year: 94	
Actual plugging report: MIRU Howco. Mixed and pumped 25 sxs. 60/40	
pozmix - 10% gel - 1/4# Flocele - 150# hulls - 12 sxs. gel. Followed by 175 sxs. cement w/250# hulls. P.S.I. 1000#. S.I.P. 700#.	
Hooked-up to 8 5/8" surface casing - pumped 25 sxs. 60/40 pozmin CF1080	
gel - 1/4# sx. Flocele and 100# hulls.	P.S.I. 200#. S.I. RNSA 200 # ORATION COMMISSION
	NAMES OF THE PARTY
	NOV 1 0 1994
Remarks:	11-10-79
Condition of casing(in hole):GOOD X E	CONSERVÁTION DIVISION ' BAD Anhy.plug:YES X NOWICHITA, KS
Bottom plug(in place):YES,CALC_X	NO Dakota plug:YES X .NO
Plugged through TUBING, CASING	X . Elevation: GL
I didky 0 tid fot)] observe the p	olugging. Senning Thames
11-18-94	(agant)
DATE 11-18-94	(agent)
UNIE	Form CP-2/3