4-041479

5-27 15-147-00490-00-00

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API number: 15- - 8-20-42

SW SE SW /4 SEC. 28, 05 S, 20 W
330 feet from S section line
3630 feet from E section line

Operator license# 5447

Lease Vehige "A" well # 4

Operator: OXY USA, Inc.

County Phillips

Address: 110 S. Main
Suite #800
Wichita, Kansas 67202

Well total depth 3614 feet 117.45
Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8 5/8 Inch @ 166 feet
w/125 sx.

Aband. oil well X, Gas well ___, Input well ___, SWD ___, D & A ___

Plugging contractor: Halliburton Cementing License# -

Address: Oberlin, Kansas

Company to plug at: Hour: 9:00A.M. Day: 27 Month: May Year: 93

Plugging proposal received from: Jim Newell

Company: OXY USA, Inc. Phone:

Were: 5 1/2" casing set @ 3614' w/125 sx. cement. Perf. @ 3533'-3560'.
Anhy. @ 1770' - Dakota @ 1100'.
Ordered 250 sxs. 60/40 pozmix - 10% gel. with 1/4# F.C. plus 500# hulls.

Plugging Proposal Received by: Dennis L. Hamel
Plugging operations attended by agent? All[ ], Part[X], None[ ]

Completed: Hour: 1:30P.M., Day: 27, Month: May, Year: 93

Actual plugging report: R.I.H. with tubing to 3507'. Spotted 25 sx. cement w/100# hulls @ 3000'. Spotted 9 sx. gel. @ 1770'. Spotted 140 sx. cement to circulate at surface. P.O.O.H. with tubing. Squeezed 50 sx. cement w/100# hulls. Max. 300#. Hooked-up to 8 5/8" Squeezed 50 sx. cememt w/100# hulls. Max. 200#.

Remarks:
Condition of casing(in hole): GOOD X BAD ___ **Anhy.plug:** YES X NO ___
Bottom plug(in place): YES X, CALC ___, NO ___ **Dakota plug:** YES X, NO ___
Plugged through TUBING X, CASING ___. **Elevation:** ___ GL

RECEIVED
STATE CORPORATION COMMISSION
JUL 14 1993
CONSERVATION DIVISION
Wichita, Kansas

07-14-93

I did [X] / did not [ ] observe the plugging. Dennis L. Hamel

(agent)

INVOICED
DATE 7-16-93
INV. NO. 38132

Form CP-2/3