4-060650 2-16 15-147-00918-00-00

STATE CORPORATION COMMISSION	API number: 15 10-15-51		
	NT CT NT /4 CTC Of OF C OO U		
CONSERVATION DIVISION - PLUGGING 200 COLORADO DERBY BUILDING	3630 /4 SEC. 31 , 05 S, 20 W get from S section line		
WICHITA, KANSAS 67202	4290 feet from E section line		
Wishiri, Iamene C. 202			
Operator license# 5447	Lease <u>Veeh "A"</u> well # <u>11</u>		
Operator: OXY USA, Inc.	County Phillips		
Address: 110 S. Main Suite #800	Well total depth <u>3658</u> feet 116 feet		
Wichita, Kansas 67202	Conductor Pipe: 0 inch 0 0 feet Surface pipe 8 5/8 Inch 0 202 feet		
Aband. oil well <u>X</u> , Gas well, Ing	out well, SWD, D & A		
Plugging contractor: Co Tools	License#		
Address:			
Company to plug at: Hour: 11:00A.M Day: 16 Month: February Year: 95 Plugging proposal received from: J.D. Hininger Company: OXY USA, Inc. Phone: 913-434-7681			
		Were: Order 355 sxs. 60/40 posmix - 10% gel and hulls. W.L.T.D. past perforations.	
Plugging Proposal Received by: Herb De			
Plugging Proposal Received by: Herb De Plugging operations attended by agent?			
	P All[X], Part[], None[]		
Plugging operations attended by agent? Completed: Hour: 12:15P.M, Day: 16, Mc Actual plugging report: 8 5/8" to 202	P All[X], Part[], None[] onth: February , Year: 95 w/250 sxs. 5 1/2" to 3655' w/150		
Plugging operations attended by agent? Completed: Hour: 12:15P.M, Day: 16, Mc Actual plugging report: 8 5/8" to 202" sxs. R.U. and perforate at 1150' and	P All[X], Part[], None[] onth: February , Year: 95 w/250 sxs. 5 1/2" to 3655' w/150 1830'. R.U. to production casing		
Plugging operations attended by agent? Completed: Hour: 12:15P.M, Day: 16, Mc Actual plugging report: 8 5/8" to 202" sxs. R.U. and perforate at 1150' and and pumped 305 sxs. cement with 400# h	P All[X], Part[], None[] onth: February , Year: 95 w/250 sxs. 5 1/2" to 3655' w/150 1830'. R.U. to production casing nulls.		
Plugging operations attended by agent? Completed: Hour: 12:15P.M, Day: 16, Mc Actual plugging report: 8 5/8" to 202" sxs. R.U. and perforate at 1150' and	All[X], Part[], None[] onth: February , Year: 95 w/250 sxs. 5 1/2" to 3655' w/150 1830'. R.U. to production casing nulls. I onto annulus and pumped 50 sxs.		
Plugging operations attended by agent? Completed: Hour: 12:15P.M, Day: 16, Mo Actual plugging report: 8 5/8" to 202" sxs. R.U. and perforate at 1150' and and pumped 305 sxs. cement with 400# h Max. P.S.I. 1200#. S.I.P. 600#. Tied	All[X], Part[], None[] onth: February , Year: 95 w/250 sxs. 5 1/2" to 3655' w/150 1830'. R.U. to production casing nulls. I onto annulus and pumped 50 sxs.		
Plugging operations attended by agent? Completed: Hour: 12:15P.M, Day: 16, Mo Actual plugging report: 8 5/8" to 202" sxs. R.U. and perforate at 1150' and and pumped 305 sxs. cement with 400# h Max. P.S.I. 1200#. S.I.P. 600#. Tied	All[X], Part[], None[] onth: February , Year: 95 w/250 sxs. 5 1/2" to 3655' w/150 1830'. R.U. to production casing nulls. I onto annulus and pumped 50 sxs.		
Plugging operations attended by agent? Completed: Hour: 12:15P.M, Day: 16, Mo Actual plugging report: 8 5/8" to 202" sxs. R.U. and perforate at 1150' and and pumped 305 sxs. cement with 400# h Max. P.S.I. 1200#. S.I.P. 600#. Tied with 100# hulls. Max. P.S.I. 200#. S	All[X], Part[], None[] onth: February , Year: 95 w/250 sxs. 5 1/2" to 3655' w/150 1830'. R.U. to production casing nulls. I onto annulus and pumped 50 sxs.		
Plugging operations attended by agent? Completed: Hour: 12:15P.M, Day: 16, Mo Actual plugging report: 8 5/8" to 202" sxs. R.U. and perforate at 1150" and and pumped 305 sxs. cement with 400# h Max. P.S.I. 1200#. S.I.P. 600#. Tied with 100# hulls. Max. P.S.I. 200#. S Remarks: Halliburton Cementing. Condition of casing(in hole): GOOD X E	Pall[X], Part[], None[] onth: February , Year: 95 w/250 sxs. 5 1/2" to 3655' w/150 1830'. R.U. to production casing nulls. I onto annulus and pumped 50 sxs. S.I.P. 50#.		
Plugging operations attended by agent? Completed: Hour: 12:15P.M, Day: 16, Mo Actual plugging report: 8 5/8" to 202" sxs. R.U. and perforate at 1150" and and pumped 305 sxs. cement with 400# h Max. P.S.I. 1200#. S.I.P. 600#. Tied with 100# hulls. Max. P.S.I. 200#. S Remarks: Halliburton Cementing. Condition of casing(in hole): GOOD X F Bottom plug(in place): YES, CALC X	All[X], Part[], None[] onth: February , Year: 95 w/250 sxs. 5 1/2" to 3655" w/150 1830". R.U. to production casing nulls. l onto annulus and pumped 50 sxs. s.I.P. 50#. BAD Anhy.plug:YES X NO Anhy.plug:		
Plugging operations attended by agent? Completed: Hour: 12:15P.M, Day: 16, Mo Actual plugging report: 8 5/8" to 202" sxs. R.U. and perforate at 1150" and and pumped 305 sxs. cement with 400# h Max. P.S.I. 1200#. S.I.P. 600#. Tied with 100# hulls. Max. P.S.I. 200#. S Remarks: Halliburton Cementing. Condition of casing(in hole): GOOD X E	All[X], Part[], None[] onth: February , Year: 95 w/250 sxs. 5 1/2" to 3655" w/150 1830". R.U. to production casing nulls. l onto annulus and pumped 50 sxs. s.I.P. 50#. BAD Anhy.plug:YES X NO Anhy.plug:		
Plugging operations attended by agent? Completed: Hour: 12:15P.M, Day: 16, Mo Actual plugging report: 8 5/8" to 202' SXS. R.U. and perforate at 1150' and and pumped 305 sxs. cement with 400# h Max. P.S.I. 1200#. S.I.P. 600#. Tied with 100# hulls. Max. P.S.I. 200#. S Remarks: Halliburton Cementing. Condition of casing(in hole): GOOD X B Bottom plug(in place): YES, CALC X Plugged through TUBING, CASING	All[X], Part[], None[] onth: February , Year: 95 w/250 sxs. 5 1/2" to 3655" w/150 1830". R.U. to production casing nulls. d onto annulus and pumped 50 sxs. S.I.P. 50#. BAD Anhy.plug:YES X No X N		
Plugging operations attended by agent? Completed: Hour: 12:15P.M, Day: 16, Mc Actual plugging report: 8 5/8" to 202' SXS. R.U. and perforate at 1150' and and pumped 305 sxs. cement with 400# h Max. P.S.I. 1200#. S.I.P. 600#. Tied with 100# hulls. Max. P.S.I. 200#. S Remarks: Halliburton Cementing. Condition of casing(in hole): GOOD X B Bottom plug(in place): YES, CALC X Plugged through TUBING, CASING	All[X], Part[], None[] onth: February , Year: 95 w/250 sxs. 5 1/2" to 3655" w/150 1830". R.U. to production casing nulls. d onto annulus and pumped 50 sxs. S.I.P. 50#. BAD Anhy.plug:YES X No X N		