4-060649 2-16

* 000043	15-141-00411-00
TÒ: STATE CORPORATION COMMISSION	API number: 15 10-26-49
CONSERVATION DIVISION - PLUGGING 200 COLORADO DERBY BUILDING	<u>SW NW NW</u> /4 SEC. <u>31 , 05 S, 20 W</u> <u>4290</u> feet from S section line
	4950 feet from E section line
•	
Operator license# 5447	Lease_Veeh "A" well #_9_
Operator: OXY USA, Inc.	County Phillips
Address: 110 S. Main Suite #800	Well total depth 3659 feet
Suite #800	Conductor Pipe: 0 inch 0 0 feet
Wichita, Kansas 67202	Surface pipe 8 5/8 Inch @ 203 feet
Aband. oil well <u>X</u> , Gas well, Input well, SWD, D & A	
Plugging contractor: Co Tools	License#
Address:	
Company to plug at: Hour: 12:30P.M Day: 16 Month: February Year: 95	
Plugging proposal received from: J.D. Hininger	
Company: OXY USA, Inc.	Phone: 913-434-7681
Were: Order 355 sxs. 60/40 posmix - 10% gel and hulls.	
W.L.T.D. past perforations.	
Plugging Proposal Received by: <u>Herb Deines</u>	
Plugging operations attended by agent? All[X], Part[], None[]	
Completed: Hour: 4:30P.M, Day: 16, Mon	nth: <u>February</u> , Year: <u>95</u>
Actual plugging report: 8 5/8" to 203' w/250 sxs. 5 1/2" to 3654' w/150	
sxs. R.U. and perforate at 1150' and 1830'. Tied onto annulus and pumped 50 sxs. cement with 100# hulls.	
Max. P.S.I. 200#. Tied onto production casing and pumped 305 sxs. of	
cement with 400# hulls. Max. P.S.I. 800#. S.I.P. 500#.	
Remarks:Halliburton Cementing.	
Condition of casing(in hole):GOOD X BAD Anhy.plug:YES X NO O	
Bottom plug(in place):YES,CALC_X_,NODakota plug:YES_X_,NO	
Plugged through TUBING, CASING	Elevation: 2233 GL
I did[N \dd dinbt[] observe the plugging.	
DATE OF G	
11 1 2 C# 1	Form CP-2/3