15-147-00912-00-00

4-041609 8-30

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API number: 15- - 7-05-42

SW NE NW /4 SEC. 31, 05 S, 20 W
990 feet from N section line
1650 feet from W section line

Operator license# 5447

Lease Veeh 'A' well # 2

Operator: OXY USA, Inc.

County Phillips

Address: 110 S. Main
Suite #800
Wichita, Kansas 67202

Well total depth 3684 feet 119.73
Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8 5/8 Inch @ 157 feet w/125 sxs.

Aband. oil well X, Gas well ___, Input well ___, SWD ___, D & A ___

Plugging contractor: Halliburton Cementing License# -

Address: Oberlin, Kansas

Company to plug at: Hour: 8:00A.M. Day: 30 Month: August Year: 94

Plugging proposal received from: Jim Nowell

Company: OXY USA, Inc. Phone:

Were: 5 1/2" casing set @ 3684' w/100 sxs. cmt. Perf. @ 3638' - 3640'. Anhy. @ 1825' - Dakota @ 1190' - W.L.M. 3640' - T.O.F. @ 2000'. Ordered 300 sxs. 60/40 pozmix - 10% gel with 1/4# F.C. plus 500# hulls.

Plugging Proposal Received by: Dennis L. Hamel
Plugging operations attended by agent? All[X], Part[ ], None[ ]

Completed: Hour: 3:00P.M, Day: 30, Month: August, Year: 94

Actual plugging report: Perf. casing at 1825' and 1190'. R.U. cementers. Pumped down casing with 250 sxs. cement with 300# hulls mixed in cement. Max. 650# P.S.I. Shut in 400#. 8 5/8" S.P. Pumped in 500 sxs. cement with 100# hulls. Max. 100# P.S.I. Shut in 100#.

Remarks:
Condition of casing(in hole): GOOD X BAD ___ Anhy.plug: YES X NO ___
Bottom plug(in place): YES X, CALC ___, NO ___ Dakota plug: YES X, NO ___
Plugged through TUBING ___, CASING X. Elevation: ___ GL

I did[X] did not[ ] observe the plugging. Dennis L. Hamel (agent) 9-14-94

RECEIVED STATE CORPORATION COMMISSION SEP 14 1994 CONSERVATION DIVISION WICHITA, KANSAS

INVOICED
DATE 9-26-94
INV. NO. 41259

KD.

Form CP-2/3