

10-15

4-041936

15-147-00614-00-00

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Number: 15- - NA

11-5-97

SW SE NW /4 SEC. 32, 05 S, 20 W
2970 feet from S section line
3630 feet from E section line

Operator license# 5447

Lease: Ray Well # B-1

Operator: OXY USA, Inc.

County: Phillips 116.25

Address: Drawer D
Plainville, Kansas 67663

Well total depth 3577 feet
Conductor Pipe: 0 inch @ 0 feet
Surface Pipe: 10 3/4 Inch 169 Feet
W/100 sxs cmt.

Aband. oil well X, Gas well, Input well, SWD, D & A

Plugging contractor: Halliburton Cementing License# -

Address: Hays, Kansas 67601

Company to plug at: Hour: 9:00 A.M. Day: 15 Month: October Year 1997

Plugging proposal received from: Rick Hockman

Company: OXY USA, Inc. Phone: 913-434-7681

Were: 5 1/2" casing set at 3577' w/100 sxs cement.
B.P. at 3226' with sand on top. Squeeze casing at 2790' - 3103' w/50 sxs Mid-Con cement not drilled out. Squeezed at 1177' - 1206' w/150 sxs drilled out and found additional holes in casing. Ordered 325 sxs Mid-Con 2 with 1/4# F.C. plus 800# hulls.

Plugging Proposal Received by: Herb Deines
Plugging operations attended by agent? All [X], Part [], None []

Completed: Hour: 1:15 P.M., Day: 15, Month: October, Year: 1997

Actual plugging report: R.I.H. with tubing at 2700'. Spotted 60 sxs cement with 400# hulls. Pulled to 1300' - spotted 100 sxs cement with 200# hulls. Pulled O.O.H. with tubing. Squeezed 5 1/2" casing with 115 sxs cement. Max. P.S.I. 350#. S.I.P. 350#. Squeezed 10 3/4" S.P. with 50 sxs cement with 100# hulls. Max. P.S.I. 200#. S.I.P. 85#. S.I.P. 200#.

Remarks:
Condition of casing(in hole): GOOD BAD X Anhy.plug: YES X NO
Bottom plug(in place): YES X, CALC, NO Dakota plug: YES X, NO
Plugged through TUBING X, CASING Elevation: G.L.

I did [X] / did not [] observe the plugging.

Dennis L. Hamel
(agent)

Form CP-2/3

INVOICED

NOV 06 1997

DATE

INV. NO. N 9450

10-15